**51GF Series** Gas Appliance Ball Valve





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	
	Job Location: Engineer: Contractor: Tag: PO#: Rep:

STANDARD MATERIALS LIST

Brass, C37700

PTFE

NPR

PTFE

Forged Brass C37700

# DESCRIPTION

The Apollo International<sup>™</sup> 51GF Series forged brass ball valves are specifically designed and certified for natural gas, manufactured and mixed gas, liquefied petroleum gases and LP gas-air mixture applications.

#### **FEATURES**

- Rated Gas Pressures of 1/2 and 5 psig
- Full Port Design Ensures Maximum Capacity
- For Natural Gas, Manufactured and Mixed Gases, LP Gas and LP Gas-Air Mixtures

# CSA LISTED

- ANSI Z21.15 (Appliance & Hose)/CGA9.1(1/2 psi)
- ASME B16.44 (5 psi)

#### **UL LISTED**

- UL 125 Flow Control Valves for LP-Gas, Guide YSDT to 250 psi max
- UL 842 Valves for Flammable Fluids, Guides YRBX, YRPV, and MHKZ to 250 psi max.


# PART NUMBER MATRIX

MODEL NUMBER	PART NUMBER	SIZE AND END CONNECTION (IN.)	BTU/HR
GB-1512A	51GF301A	1/2" FNPT x 1/2" FNPT	185755
GB-1534A	51GF401A	3/4" FNPT x 3/4" FNPT	437019

# DIMENSIONS

MODEL NUMBER	PART NUMBER	DIMENSIONS (IN.)			WT.
		А	В	с	(LB.)
GB-1512A	51GF301A	2.087	1.378	1.280	0.381
GB-1534A	51GF401A	2.244	1.575	1.280	0.638

# RETAINER Forged Brass, C37700 HANDLE Die Cast Aluminum NUT Steel, Plated



BODY

BALL

SEAT

STEM PACKING

This specification is provided for reference only. Apollo reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Apollo products previously or subsequently sold. Most current information available at apollovalves.com.

