

Kerotest Model-1 Gate Valve

Flanged End—500 WOG/740 MOP, Natural Gas



Product Brief

The Kerotest Model-1 Steel Gate Valves feature metal-to-metal seats, some of the lowest operating torque in the industry and a packing designed to protect the environment. Choose from a full size range of 1-inch to 16-inch with a variety of end configurations and a pressure rating from 285 to 740 psi.

Customize your gate valves with locking devices, watertight high head extensions, operating square extensions, malleable iron circular hand-wheels, indicators, epoxy coating, body bleed taps, vent pipes.

Features/Benefits

- Absolutely no maintenance
- No gland tightening
- No lubrication
- No adjustment of any kind
- Full opening—no significant pressure drop
- Lowest operating torque in the industry
- Steel—safety
- Seat test at 110% of rated pressure;
shell test at 150% of rated pressure
- 2-inch operation square malleable iron
- Buna-N™ O-Rings and V-Rings
- Brass packing actuator
- Steel packing gland cover
- Steel bonnet ASTM A-216 Grade WCB
- Stainless steel stem
- Alloy steel cap screws—ASTM A-574
- Soft iron bonnet gasket
(refinery gasket—fire proof)
- Steel body—ASTM A-216 Grade WCB



An Employee-Owned Company

Kerotest Model-1 Gate Valve Flanged End—500 WOG/740 MOP, Natural Gas

Ordering

Ordering Code Table—500 PSI

Size (in)	Valve Number	Pressure	Approx. Weight (lb)
2	1F5	500 WOG	40
3	1F5	500 WOG	40
4	1F5	500 WOG	102
6	1F5	500 WOG	182

Ordering Code Table—740 PSI

Size (in)	Valve Number	Pressure	Approx. Weight (lb)
2	1F7	300 ANSI 740 MOP	41
3	1F7	300 ANSI 740 MOP	72
4	1F7	300 ANSI 740 MOP	114
6	1F7	300 ANSI 740 MOP	198
8	1F7	300 ANSI 740 MOP	310
10	1F7	300 ANSI 740 MOP	530
12	1F7	300 ANSI 740 MOP	745
16	1F7	300 ANSI 740 MOP	2035

Note: Valves built prior to July 10, 2006 have Class 300 API, 720 MOP rating.

Materials

Name of Part	Description of Material
Body	Cast steel, ASTM A216, GR. WCB
Cover	Cast steel, ASTM A216, GR. WCB
Wedge	Cast iron, ASTM A216, GR. B
Stem	Stainless steel, ASTM A581 or A582, Type 416 or 410
Gland	Carbon steel
Packing adapter	Brass
Packing set	Buna-N™
Packing shim	Compressed fiber
Gland gasket	Compressed fiber
Cover gasket	Corrugated steel
Operating square	Cast ductile iron, ASTM A536, GR. 65-45-12
Thrust washer	Brass, SAE 706
O-Ring	Buna-N
Hex head cap screw	Steel, SAE GR. 5
Hex socket head cap screw	Steel, ASTM A574
Hex nut	Steel, zinc plated
Drive screw	Stainless steel
Rating tag	18-8 Stainless steel
Nameplate	18-8 Stainless steel

Dimensions

Size (in)	End-to-End (in)	C/L-to-Top (in)	Number of Turns	Temperature (°F)
2	8-1/2	8-3/4	7-1/4	-20 to +200
3	11-1/8	10-7/16	10-1/4	
4	12	12-11/16	13-3/4	
6	15-7/8	16-7/16	19-3/4	
8	16-1/2	20-1/4	26-1/4	
10	18	27	21-3/4	
12	19-3/4	30-3/4	25-3/4	
16	33	41-3/8	69	

All product names referenced herein are trademarks of their respective companies.



Kerotest Manufacturing Corp.

5500 Second Avenue • Pittsburgh, PA 15207
412.521.4663 • Fax: 412.521.5990
www.Kerotest.com • Sales@Kerotest.com