

Stainless Steel Ball Valves with Spring Return Handle

Spring Return Handle to Close • Two-Piece Investment Cast Body • Full Port • Blowout-Proof Stem • 316 SS Trim • Vented Ball

1000 PSI/69 bar non-shock cold working pressure

CONFORMS TO MSS SP-110 & NACE MR0175

MATERIAL LIST


| PART | SPECIFICATION | | | | |
|-------------------------------|---|--|--|--|--|
| 1. Handle Nut | Stainless Steel Type 304 | | | | |
| 2. Stem | Stainless Steel Type 316 | | | | |
| 3. Lock Washer | Stainless Steel Type 304 | | | | |
| 4. Threaded Pack Gland | Stainless Steel Type 316 | | | | |
| 5. Thrust Washer | Carbon Filled PTFE | | | | |
| 6. Gasket | Reinforced PTFE | | | | |
| 7. Body End Piece | Stainless Steel ASTM A351 Type CF8M | | | | |
| 8. Ball (Vented) | Stainless Steel ASTM A276 Type 316 or ASTM A351 Type CF8M | | | | |
| 9. Seats (2) | Reinforced PTFE | | | | |
| 10. Body | Stainless Steel ASTM A351 Type CF8M | | | | |
| 11. Stem Packing | Carbon Filled PTFE | | | | |
| 12. Handle | Stainless Steel Type 316 & 304 w/Vinyl Cover | | | | |
| 13. Mounting Plate | Stainless Steel ASTM A351 Type CF8M | | | | |
| 14. Socket Head Cap Screw (2) | Stainless Steel Type 304 | | | | |

NOTE: Valves are static grounded by thrust washer and packing. Valves tested in accordance with ASME B16.34



T-585-S6-R-66-SR

Threaded



DIMENSIONS—WEIGHTS—QUANTITIES

| | Dimensions | | | | | | | | | |
|-----|------------|------------|------------|------------|------------|-------------|-------------|-------------|----------------|-----------|
| S | ize | Α | B | D | H | L | LA | LB T | -585-S6-R-66-S | SR Master |
| ln. | mm. | In. mm. | In. mm. | In. mm. | In. mm. | In. mm. | In. mm. | In. mm. | Lbs. Kg. | Ctn. Qty. |
| 1/4 | 8 | 2.20 56.00 | 1.10 28.00 | 0.43 11.00 | 1.68 42.75 | 7.09 180.00 | 4.88 123.93 | 5.74 145.85 | 0.60 0.27 | 10 |
| 3/8 | 10 | 2.20 56.00 | 1.10 28.00 | 0.43 11.00 | 1.68 42.75 | 7.09 180.00 | 4.88 123.93 | 5.74 145.85 | 0.75 0.34 | 10 |
| 1/2 | 15 | 2.60 66.00 | 1.26 32.00 | 0.56 14.20 | 1.75 44.65 | 7.09 180.00 | 4.88 123.93 | 5.74 145.85 | 1.34 0.61 | 8 |
| 3/4 | 20 | 2.99 76.00 | 1.65 42.00 | 0.81 20.50 | 2.10 53.25 | 7.28 185.00 | 4.92 124.99 | 5.98 151.86 | 2.05 0.93 | 6 |
| _1_ | 25 | 3.54 90.00 | 2.05 52.00 | 1.00 25.40 | 2.27 57.65 | 7.28 185.00 | 4.92 124.99 | 5.98 151.86 | 2.05 0.93 | 6 |

[◆]For detailed operating pressure, refer to pressure temperature chart on pages 66 and 67 in the Ball catalog.



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Visit our website for the most current information.