
WALWORTH CAST IRON RISING STEM GLOBE VALVES CLASS 250

DESIGN FEATURES

- Design in accordance with MSS SP-85
- CLASS 250
- Rising Stem
- Cast Iron Construction
- Bolted Body design
- Handwheel Operated
- Face to Face dimensions as per ANSI B16.10
- Flanged drilled as per ANSI B16.1

Catalog Figure No.	Type of Ends
W8955F	Flat Face ends







Dimensions and Weights

D Nominal Diameter	mm	51	64	76	102	127	152	203	254	305
	in	2	2 1/2	3	4	5	6	8	10	12
A	mm	267.0	292.0	318.0	356.0	400.0	444.0	533.0	622.0	711.0
	inch	10.51	11.50	12.52	14.02	15.75	17.48	20.98	24.49	27.99
B (Open)	mm	286	311	334	394	457	514	584	610	718
	inch	11.25	12.25	13.13	15.50	18.00	20.25	23.00	24.00	28.25
C	mm	175	200	254	300	300	348	400	457	457
	inch	6.89	7.87	10.00	11.81	11.81	13.70	15.75	17.99	17.99
E	mm	165.0	191.0	210.0	254.0	279.0	318.0	381.0	445.0	521.0
	inch	6.50	7.52	8.27	10.00	10.98	12.52	15.00	17.52	20.51
Weight	kg	28	34	46	76	101	132	201	317	433
W8955F	lb	61.74	74.97	101.43	167.59	222.71	291.07	443.22	699.01	954.80
Cv	Flow Coefficient	47.0	76.0	109.0	199.0	320.0	477.0	877.0	1370.0	2048.0