




0800B-1500B Gate Valves

Forged Steel OS&Y – Conventional Port
Valves comply with applicable portions of API 602 and ASME B16.34

Class 800
1/2" - 2"



0800B

* Also available in Class 1500, see below for dimensional information

CLASS 800 CONVENTIONAL PORT BOLTED BONNET GATE VALVE - BUTT WELD ENDS-INCHES (MM)					
VALVE SIZE NPS (DN)	END TO END	CENTER TO TOP (OPEN)	HANDWHEEL DIAMETER	PORT DIAMETER	APPROX. WEIGHT LBS (KG)
1/2 (15)	3.25 (83)	6.31 (160)	4.00 (102)	0.31 (8)	3.8 (1.7)
3/4 (20)	3.50 (89)	6.50 (165)	4.00 (102)	0.50 (13)	4.5 (2.0)
1 (25)	3.88 (98)	7.25 (184)	4.00 (102)	0.66 (17)	6.3 (2.8)
1 1/4 (32)	4.75 (121)	9.13 (232)	5.50 (140)	1.19 (30)	9.5 (4.3)
1 1/2 (40)	4.75 (121)	9.13 (232)	5.50 (140)	1.19 (30)	12.0 (5.4)
2 (50)	5.50 (140)	11.06 (281)	6.63 (168)	1.50 (38)	20.5 (9.3)

CLASS 1500 CONVENTIONAL PORT BOLTED BONNET GATE VALVE - BUTT WELD ENDS-INCHES (MM)					
VALVE SIZE NPS (DN)	END TO END	CENTER TO TOP (OPEN)	HANDWHEEL DIAMETER	PORT DIAMETER	APPROX. WEIGHT LBS (KG)
1/2 (15)	3.50 (89)	6.50 (165)	4.00 (102)	0.31 (8)	5.0 (2.3)
3/4 (20)	3.88 (98)	7.25 (184)	4.00 (102)	0.50 (13)	7.3 (3.3)
1 (25)	4.75 (121)	8.94 (227)	5.50 (140)	0.66 (17)	14.0 (6.4)
1 1/4 (32)	5.50 (140)	11.00 (279)	6.63 (168)	1.19 (30)	23.0 (10.4)
1 1/2 (40)	5.50 (140)	11.00 (279)	6.63 (168)	1.19 (30)	22.5 (10.2)
2 (50)	6.25 (159)	11.56 (294)	6.63 (168)	1.50 (38)	29.5 (13.4)