





OC81-SC81-OC83-SC83-OC86-SC86 Check Valves

Forged Steel, Bolted Cap, Horizontal, Piston-type
Valves comply with applicable portions of API 602 and ASME B16.34


Class 150/300/600
1/2" - 2"




OC81




SC81




OC83



SC83



OC86



SC86



OC81 CLASS 150 BOLTED CAP PISTON TYPE CHECK VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DIN)	FACE TO FACE	CENTER TO TOP (OPEN)	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WEIGHT LBS (KG)	CRACKING PRESSURE PSI (BAR)
1/2 (15)	4.25 (108)	1.88 (48)	0.38 (10)	3.54 (90)	1.38 (35)	4	0.63 (16)	2.38 (60)	4.4 (2.0)	0.7 (0.05)
3/4 (20)	4.63 (118)	2.00 (51)	0.50 (13)	3.94 (100)	1.69 (43)	4	0.63 (16)	2.75 (70)	5.5 (2.5)	0.7 (0.05)
1 (25)	5.00 (127)	2.56 (65)	0.69 (17)	4.25 (108)	2.00 (51)	4	0.63 (16)	3.13 (79)	8.8 (4.0)	0.7 (0.05)
1 1/2 (40)	6.50 (165)	2.94 (75)	1.19 (30)	5.00 (127)	2.88 (73)	4	0.63 (16)	3.88 (98)	17.6 (8.0)	0.8 (0.05)
2 (50)	8.00 (203)	3.75 (95)	1.44 (37)	6.00 (152)	3.63 (92)	4	0.75 (19)	4.75 (121)	25.4 (11.5)	0.7 (0.05)

SC81 CLASS 150 BOLTED CAP SPRING PISTON TYPE CHECK VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DIN)	FACE TO FACE	CENTER TO TOP (OPEN)	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WEIGHT LBS (KG)	CRACKING PRESSURE PSI (BAR)
1/2 (15)	4.25 (108)	1.88 (48)	0.38 (10)	3.54 (90)	1.38 (35)	4	0.63 (16)	2.38 (60)	4.4 (2.0)	1.6 (0.11)
3/4 (20)	4.63 (118)	2.00 (51)	0.50 (13)	3.94 (100)	1.69 (43)	4	0.63 (16)	2.75 (70)	5.5 (2.5)	2.1 (0.15)
1 (25)	5.00 (127)	2.56 (65)	0.69 (17)	4.25 (108)	2.00 (51)	4	0.63 (16)	3.13 (79)	8.8 (4.0)	2.0 (0.13)
1 1/2 (40)	6.50 (165)	2.94 (75)	1.19 (30)	5.00 (127)	2.88 (73)	4	0.63 (16)	3.88 (98)	17.6 (8.0)	2.5 (0.17)
2 (50)	8.00 (203)	3.75 (95)	1.44 (37)	6.00 (152)	3.63 (92)	4	0.75 (19)	4.75 (121)	25.4 (11.5)	2.6 (0.18)



OC81-SC81-OC83-SC83-OC86-SC86 Check Valves

Forged Steel, Bolted Cap, Horizontal, Piston-type
Valves comply with applicable portions of API 602 and ASME B16.34

Class 150/300/600
1/2" - 2"

OC83 CLASS 300 BOLTED CAP PISTON TYPE CHECK VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DIN)	FACE TO FACE	CENTER TO TOP (OPEN)	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WEIGHT LBS (KG)	CRACKING PRESSURE PSI (BAR)
1/2 (15)	6.00 (152)	2.00 (51)	0.38 (10)	3.75 (95)	1.38 (35)	4	0.63 (16)	2.63 (67)	5.8 (2.6)	0.3 (0.02)
3/4 (20)	7.00 (178)	2.25 (57)	0.50 (13)	4.63 (118)	1.69 (43)	4	0.75 (19)	3.25 (83)	9.5 (4.3)	0.3 (0.02)
1 (25)	8.00 (203)	2.63 (67)	0.75 (19)	4.92 (125)	2.00 (51)	4	0.75 (19)	3.50 (89)	13.3 (6.0)	0.3 (0.02)
1 1/2 (40)	9.00 (229)	3.69 (94)	1.19 (30)	6.13 (156)	2.88 (73)	4	0.88 (22)	4.50 (114)	28.8 (13.0)	0.3 (0.02)
2 (50)	10.50 (267)	4.25 (108)	1.44 (37)	6.50 (165)	3.63 (92)	8	0.75 (19)	5.00 (127)	37.0 (16.8)	0.4 (0.03)

SC83 CLASS 300 BOLTED CAP SPRING PISTON TYPE CHECK VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DIN)	FACE TO FACE	CENTER TO TOP (OPEN)	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WEIGHT LBS (KG)	CRACKING PRESSURE PSI (BAR)
1/2 (15)	6.00 (152)	2.00 (51)	0.38 (10)	3.75 (95)	1.38 (35)	4	0.63 (16)	2.63 (67)	5.8 (2.6)	1.8 (0.12)
3/4 (20)	7.00 (178)	2.25 (57)	0.50 (13)	4.63 (118)	1.69 (43)	4	0.75 (19)	3.25 (83)	9.5 (4.3)	1.0 (0.07)
1 (25)	8.00 (203)	2.63 (67)	0.75 (19)	4.92 (125)	2.00 (51)	4	0.75 (19)	3.50 (89)	13.3 (6.0)	0.6 (0.04)
1 1/2 (40)	9.00 (229)	3.69 (94)	1.19 (30)	6.13 (156)	2.88 (73)	4	0.88 (22)	4.50 (114)	28.8 (13.0)	0.5 (0.03)
2 (50)	10.50 (267)	4.25 (108)	1.44 (37)	6.50 (165)	3.63 (92)	8	0.75 (19)	5.00 (127)	37.0 (16.8)	0.7 (0.05)

OC86 CLASS 600 BOLTED CAP PISTON TYPE CHECK VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DIN)	FACE TO FACE	CENTER TO TOP (OPEN)	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WEIGHT LBS (KG)	CRACKING PRESSURE PSI (BAR)
1/2 (15)	6.50 (165)	2.00 (51)	0.38 (10)	3.75 (95)	1.38 (35)	4	0.63 (16)	2.63 (67)	6.3 (2.8)	0.3 (0.02)
3/4 (20)	7.50 (191)	2.25 (57)	0.50 (13)	4.63 (118)	1.69 (43)	4	0.75 (19)	3.25 (83)	10.5 (4.8)	0.3 (0.02)
1 (25)	8.50 (216)	2.63 (67)	0.75 (19)	4.94 (125)	2.00 (51)	4	0.75 (19)	3.50 (89)	13.5 (6.1)	0.3 (0.02)
1 1/2 (40)	9.50 (241)	3.69 (94)	1.19 (30)	6.13 (156)	2.88 (73)	4	0.88 (22)	4.50 (114)	29.5 (13.4)	0.3 (0.02)
2 (50)	11.50 (292)	4.25 (108)	1.44 (37)	6.50 (165)	3.63 (92)	8	0.75 (19)	5.00 (127)	43.5 (19.7)	0.4 (0.03)

SC86 CLASS 600 BOLTED CAP SPRING PISTON TYPE CHECK VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DIN)	FACE TO FACE	CENTER TO TOP (OPEN)	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WEIGHT LBS (KG)	CRACKING PRESSURE PSI (BAR)
1/2 (15)	6.50 (165)	2.00 (51)	0.38 (10)	3.75 (95)	1.38 (35)	4	0.63 (16)	2.63 (67)	6.3 (2.8)	1.8 (0.12)
3/4 (20)	7.50 (191)	2.25 (57)	0.50 (13)	4.63 (118)	1.69 (43)	4	0.75 (19)	3.25 (83)	10.5 (4.8)	1.0 (0.07)
1 (25)	8.50 (216)	2.63 (67)	0.75 (19)	4.92 (125)	2.00 (51)	4	0.75 (19)	3.50 (89)	13.5 (6.1)	0.6 (0.04)
1 1/2 (40)	9.50 (241)	3.69 (94)	1.19 (30)	6.13 (156)	2.88 (73)	4	0.88 (22)	4.50 (114)	29.5 (13.4)	0.5 (0.03)
2 (50)	11.50 (292)	4.25 (108)	1.44 (37)	6.50 (165)	3.63 (92)	8	0.75 (19)	5.00 (127)	43.5 (19.7)	0.7 (0.05)