




0895-0895B Gate Valves

Forged Steel OS&Y – Full Port


Valves comply with applicable portions of API 602 and ASME B16.34

Class 1500

1/2" - 2"



0895



0895B

CLASS 1500 FULL PORT BOLTED BONNET GATE VALVE - FLANGED ENDS - INCHES (MM)

VALVE SIZE NPS (DN)	FACE TO FACE	CENTER TO TOP (OPEN)	HANDWHEEL DIAMETER	PORT DIAMETER	FLANGE DIAMETER	RAISED DIAMETER	BOLT HOLE	BOLT HOLE DIAMETER	BOLT CIRCLE	APPROX. WT. LBS (KG)
1/2 (15)	8.50 (216)	8.18 (208)	4.00 (102)	0.50 (13)	4.75 (121)	1.38 (35)	4	0.88 (22)	3.25 (83)	17.0 (7.7)
3/4 (20)	9.00 (229)	9.47 (241)	5.50 (140)	0.75 (19)	5.13 (130)	1.69 (43)	4	0.88 (22)	3.50 (89)	23.0 (10.4)
1 (25)	10.00 (254)	9.93 (252)	5.50 (140)	0.94 (24)	5.88 (149)	2.00 (51)	4	1.00 (25)	4.00 (102)	34.0 (15.4)
1 1/2 (40)	12.00 (305)	12.82 (326)	6.63 (168)	1.50 (38)	7.00 (178)	2.88 (73)	4	1.13 (29)	4.88 (124)	54.0 (24.5)
2 (50)	14.50 (368)	13.46 (342)	6.63 (168)	2.00 (51)	8.50 (216)	3.63 (92)	8	1.00 (25)	6.50 (165)	97.0 (44.0)

CLASS 1500 FULL PORT BOLTED BONNET GATE VALVE - BUTT WELD - INCHES (MM)

VALVE SIZE NPS (DN)	END TO END	CENTER TO TOP (OPEN)	HANDWHEEL DIAMETER	PORT DIAMETER	APPROX. WEIGHT LBS (KG)
1/2 (15)	8.50 (216)	8.18 (208)	4.00 (102)	0.50 (13)	13.6 (6.2)
3/4 (20)	9.00 (229)	9.47 (241)	4.00 (102)	0.75 (19)	18.4 (8.4)
1 (25)	10.00 (254)	9.93 (252)	5.50 (140)	0.94 (24)	27.4 (12.4)
1 1/2 (40)	12.00 (305)	12.82 (326)	6.63 (168)	1.50 (38)	43.6 (19.8)
2 (50)	14.50 (368)	13.46 (342)	6.63 (168)	2.00 (51)	79.9 (36.2)