



Triple-offset Butterfly Valves

L&T Valves offers a comprehensive range of Triple-offset Butterfly Valves in a variety of body styles and materials to address critical process requirements in diverse industries such as hydrocarbon, power, chemicals & fertiliser, water, etc.

The product range covers valves in ASME classes up to 1500, in sizes up to 100" (2500 mm), in carbon steel, stainless steel and alloy steels, suitable for temperatures from -196°C to 538°C. Based on customer requirements, valves in higher pressure classes, larger sizes and other materials are also offered.

The metal-seated valves conform to API 609 Category B and offer high-integrity bi-directional sealing.



L&T Valves offers Fabricated Steel Triple-offset Butterfly Valves for water industry in pressure classes from PN 6 to PN 25, in sizes up to 100" (2500 mm)

Flanged - Short and Long Patterns

ASME Class	3	4	6	8	10	12	14	16	18	20	24	26	28	30	32	34	36	38	40	42	48	54	64	72	84	100
	80	100	150	200	250	300	350	400	450	500	600	650	700	750	800	850	900	950	1000	1050	1200	1350	1600	1800	2100	2500
150	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
300	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
600	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
900	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1500	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Wafer and Wafer-Lugged

ASME Class	3	4	6	8	10	12	14	16	18	20	24
	80	100	150	200	250	300	350	400	450	500	600
150	•	•	•	•	•	•	•	•	•	•	•
300	•	•	•	•	•	•	•	•	•	•	•
600	•	•	•	•	•	•	•	•	•	•	•