



Fig No. 53 - Gate Valve (Non-rising stem, Screw End)

Size: DN15 - 50
 Working Pressure: 16 bar
 Working Temp.: -10 ~ 100°C
 Body/Bonnet/Disc: Bronze (BS EN 1982)
 Stem: Brass (BS EN 12164)
 Handwheel: Aluminum



Fig No. 108 - Gate Valve (Non-rising stem, Screw End)

Size: DN15 - 50
 Working Pressure: 25 bar
 Working Temp.: -10 ~ 100°C
 Body/Bonnet/Disc: Bronze (BS EN 1982)
 Stem: Brass (BS EN 12164)
 Handwheel: Aluminum



Fig No. 55 - Globe Valve (Rising stem, Screw End)

Size: DN15 - 50
 Working Pressure: 16 bar
 Working Temp.: -10 ~ 100°C
 Body/Bonnet/Disc: Bronze (BS EN 1982)
 Stem/Disc: Brass (BS EN 12164)
 Handwheel: Aluminum



Fig No. 54 - Swing Check Valve (Screw End)

Size: DN15 - 50
 Working Pressure: 16 bar
 Working Temp.: -10 ~ 100°C
 Body: Bronze (BS EN 1982)
 Disc: Bronze (BS EN 1982)



Fig No. 56 - Y-Strainer

Size: DN15 - 50
 Working Pressure: 25 bar
 Working Temp.: -10 ~ 100°C
 Body: Bronze (BS EN 1982)
 Screen: Stainless Steel 304 (BS EN 10088-1)