

Fig No. 139 - Wafer Type Butterfly Valve (with lever)



Size: DN50 - 200
 Working Pressure: 16 bar
 Working Temp.: <120°C
 Body: Cast Iron w/ Epoxy
 Stem: Stainless Steel 431
 Disc: Ductile Iron w/ nickel plated, or
 Stainless Steel 316

Fig No. 140 - Wafer Type Butterfly Valve (gear box with handwheel)



Size: DN50 - 500
 Working Pressure: 16 bar
 Working Temp.: < 120°C
 Body: Cast Iron w/ Epoxy (DN50-300) / Ductile Iron w/ Epoxy (DN350-500)
 Stem: Stainless Steel 431 (DN50-300) / Stainless Steel 410 (DN350-500)
 Disc: Ductile Iron w/ nickel plated, or
 Stainless Steel 316

Fig No. 142 - Lug Type Butterfly Valve (with lever)



Size: DN50 - 200
 Working Pressure: 16 bar
 Working Temp.: <120°C
 Body: Ductile Iron w/ Epoxy
 Stem: Stainless Steel 431
 Disc: Ductile Iron w/ nickel plated, or
 Stainless Steel 316

Fig No. 143 - Lug Type Butterfly Valve (gear box with handwheel)



Size: DN50 - 500
 Working Pressure: 16 bar
 Working Temp.: < 120°C
 Body: Ductile Iron w/ Epoxy
 Stem: Stainless Steel 431 (DN50-300) / Stainless Steel 410 (DN350-500)
 Disc: Ductile Iron w/ nickel plated, or
 Stainless Steel 316

Fig No. 140SP / 143SP - Butterfly Valve with Electric Actuator



Size: DN50 - 500
 Working Pressure: 16 bar
 Working Temp.: < 120°C
 Body: Cast Iron w/ Epoxy (DN50-300) / Ductile Iron w/ Epoxy (DN350-500)
 Stem: Stainless Steel 431 (DN50-300) / Stainless Steel 410 (DN350-500)
 Disc: Ductile Iron w/ nickel plated, or
 Stainless Steel 316
 Electric Actuator: "TTT" QT series electric actuator for on/off