


FORGED STEEL VALVES

DOUGLAS CHERO SpA
dc FORGED VALVES





Ratings (ASTM A105)
800 p.s.i. @ 850 F
1975 p.s.i. @ 100 F

Test pressure (ASTM A105)
Hydraulic: (minimum)
Body - 3000 p.s.i.
Seat - 2175 p.s.i.
Air under water:
Seat - 85 p.s.i.

Standards
Construction founded on API 602, BS 5352
Socket weld ASME B16.11
Threaded ASME B1.20.1
Test founded on API 598-BS 6755 (Pt.1)

Connections (xx)	
SW Socket weld	B8 Butt weld 80
TH Threaded NPT	
TS Sw/NPT	
SE Sw(e)/NPT	
SU Sw(u)/NPT	
B4 Butt weld 40	

CONVENTIONAL BORE								
			1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
Ff (mm/in)			80 3,15	90 3,54	110 4,33	127 5,00	127 5,00	130 5,12
Ha (mm/in)			333 13,11	367 14,45	406 15,98	463 18,23	508 20,00	534 21,02
VI (mm/in)			90 3,54	90 3,54	100 3,94	120 4,72	140 5,51	140 5,51
Pf (mm/in)			10 0,39	14 0,55	18 0,71	24 0,94	31 1,22	36,5 1,44
Wt. (kg/lb)			3,1 6,8	3,6 7,9	5,7 12,5	8,8 19,4	11,7 25,7	14,4 31,7
Catal. no.			CR252/xx	CR253/xx	CR254/xx	CR255/xx	CR256/xx	CR257/xx

FULL BORE								
	1/4"	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
Ff (mm/in)	80 3,15	80 3,15	90 3,54	110 4,33	127 5,00	127 5,00	130 5,12	150 5,91
Ha (mm/in)	330 12,99	333 13,11	367 14,45	406 15,98	463 18,23	508 20,00	534 21,02	658 25,91
VI (mm/in)	90 3,54	90 3,54	90 3,54	100 3,94	120 4,72	140 5,51	140 5,51	200 7,87
Pf (mm/in)	9 0,35	10 0,39	14 0,55	18 0,71	24 0,94	31 1,22	36,5 1,44	48 1,89
Wt. (kg/lb)	3,1 6,8	3,1 6,8	3,6 7,9	5,7 12,5	8,8 19,4	11,7 25,7	14,4 31,7	22,2 48,8
Catal. no.	CF210/xx	CF211/xx	CF212/xx	CF213/xx	CF214/xx	CF215/xx	CF216/xx	CF217/xx

1) Standard and alternative valve materials on page 67, type C
 2) Complete Pressure-Temperature ratings on page 68, 69, 70, 71,72
 3) SW & NPT dimensions on page 73
 4) On request flanged ends can be supplied; body dimensions on page 5,6,7
 5) For Ha Length in according to customer desire extension should be welded