

# **70B-140 Series**

Power Piping Bronze Ball Valve





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

### **DESCRIPTION**

The Apollo 70B Series for boiler external piping service has the same rugged features as the standard 70 Series valves but with ASTM B62 bronze shell components. The 70B provides trusted performance along with a wide range of options to suit every application.

### **FEATURES**

- · Blowout-Proof Stem Design
- Adjustable Packing Gland
- MPTFE Seats and Stuffing Box
- 100% Factory Tested

### PERFORMANCE RATING

- Maximum Pressure: CWP: 600 psig | SWP: 250 psig
- Maximum Temperature: 500°F
- Vacuum Service to 29 in. Hg

### **APPROVALS**

- MSS SP-110; Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends
- CRN: OC10908.5C
- ASME B31.1, "Power Piping"

## OPTIONS

•	(-02) Stem Grounded	3/4" - 2
•	(-03) 1-1/4" CS Stem Extension	3/4" - 2
	(-04) 2-1/4" CS Stem Extension	3/4" - 2
•	(-07) Steel Tee Handle	3/4" - 2
•	(-08) 90° Reversed Stem	3/4" - 2
•	(-10) SS Lever & Nut	3/4" - 2
	(-14) Side Vented Ball (Uni-Directional)	3/4" - 2
•	(-15) Wheel Handle, Steel	3/4" - 2
•	(-16) Chain Lever-Vertical	3/4" - 2
•	(-24) Graphite Packing	3/4" - 2
•	(-27) SS Latch-Lock Lever & Nut	3/4" - 2
•	(-30) Cam-Lock & Grounded	3/4" - 2
•	(-32) SS Tee Handle & Nut	3/4" - 2
•	(-39) SS Hi-Rise Locking Wheel Handle & Nut	3/4" - 2
•	(-40) Cyl-Loc & Grounded	3/4" - 2
•	(-45) Less Lever & Nut	3/4" - 2'
•	(-46) Latch Lock Lever-Lock Closed Position Only	3/4" - 2
•	(-47) SS Oval Latch-Lock Handle & Nut	3/4" - 1"
•	(-48) SS Oval Handle (No Latch) & Nut	3/4" - 2'
•	(-49) Assembled Dry	3/4" - 2
•	(-50) 2-1/4" CS Locking Stem Extension	3/4" - 2
•	(-57) Oxygen Cleaned	3/4" - 2
•	(-58) Chain Lever-Horizontal	3/4" - 2
•	(-60) Static Grounded Ball & Stem	3/4" - 2'
•	(-P01) BSPP (Parallel) Threaded Connection	1/4' - 2"
•	(-T01) BSPT (Tapered) Threaded Connection	1/4' - 2"

### STANDARD MATERIALS LIST

Steel, Zinc Plated w/ Vinyl				
MPTFE				
RPTFE				
Brass, C37700, Chrome Plated A276-316				
MPTFE				
Bronze, B505-C83600 (1/4" to 1") ASTM B154 Bronze, B62-C83600 (1-1/4" - 2") ASTM B154				
Brass, C36000				
A276-316				
Steel, Zinc Plated				
Bronze, B62-C83600				

### **DIMENSIONS**

PART CITE (IN)		DIMENSIONS (IN.)					
NUMBER	SIZE (IN.)	Α	В	С	D	E	WT. (LB.)
70B-141-64	1/4"	0.37	1.03	2.06	1.75	3.87	0.60
70B-142-64	3/8"	0.37	1.03	2.06	1.75	3.87	0.56
70B-143-64	1/2"	0.50	1.12	2.25	1.75	3.87	0.63
70B-144-64	3/4"	0.68	1.50	3.00	2.12	4.87	1.39
70B-145-64	1"	0.87	1.68	3.37	2.25	4.87	1.72
70B-146-64	11/4"	1.00	2.00	4.00	2.62	5.50	3.26
70B-147-64	11/2"	1.25	2.18	4.37	3.06	8.00	4.61
70B-148-64	2"	1.50	2.34	4.68	3.25	8.00	6.06



