1.00
[25.4]

1.00
[25.4]

SENSING
AREA

2.42
[61.5]

3.24
[82.2]

2X Ø.20
[Ø5.2]

.56
[14.3]

SENSING
AREA

GO
SWITCH™

SPDT
4A @ 120VAC
3A @ 24VDC
RESISTIVE

CE

CCC

COUNTRY OF ORIGIN
US
TopWorx
www.topworx.com

SERIAL NO.

MODEL NO.

## MODEL NUMBER

31-17524-A2

### PRODUCT LINE

GO™ Switch Model 31

### SPECIFICATIONS

| | |
|---|---|
| Model | 31 Model |
| Contact Form | SPDT (Form C) |
| Sensing Range | Approx. 1/4" end sensing |
| Outlet Position | 1/2"-14NPT conduit hub bottom |
| Enclosure Material | Stainless steel |
| Area Classification | cUL Cl I Div 1 |
| Wiring Options | 3ft PVC lead wires |
| Regional Certification | No regional certification |
| Custom Field | TopWorx Certified: IP 66/67/68, NEMA 4x/6/6P |

### WIRING DIAGRAM

PVC/PTFE LEADS – 4 WIRE
SPDT

RED
BLACK
BLUE
GREEN

Current as of August 31, 2021 – Subject to change without notice.

### NAMEPLATE

GO
SWITCH
www.topworx.com
COUNTRY OF ORIGIN US

CE

CCC

50

UL
CERTIFIED

SÉCURITÉ CA
E79070

Cl I, Div 1, Grps A-D; Type 4X
Cl II, Div 1, Grps E-G; Cl III;
120VAC/4A, 24VDC/3A
LEAD SEAL REQUIRED

Model #: _____          Serial #: _____

GO
SWITCH™

**TOPWORX**
3300 Fern Valley Road
Louisville, KY 40213

(502)969-8000 PH
(502)969-5911 FAX
www.topworx.com