







	Figure Number	Trim Code	Action	Part No	Inventory Description	In Stock
	Figure 990	102 (EPDM)		990025102WM4B00	25mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mulling Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	6
	Figure 990	102 (EPDM)		990040102WM4B00	40mm (1 1/2") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mulling Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	8
	Figure 990	102 (EPDM)		990050102WM4B00	50mm (2") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mulling Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	7
	Figure 990	102 (EPDM)		990065102WM4B00	25mm (2 1/2") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mulling Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	6
	Figure 990	102 (EPDM)		990080102WM4B00	80mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mulling Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	14

KEYSTONE STOCKLIST

	Figure 990	102 (EPDM)		990100102WM4B00	100mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mounting Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	15
	Figure 990	102 (EPDM)		990125102WM4B00	125mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mounting Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	9
	Figure 990	102 (EPDM)		990150102WM4B00	150mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mounting Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	18
	Figure 990	102 (EPDM)		990200102WM4B00	200mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mounting Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	2
	Figure 990	102 (EPDM)		990250102WM4B00	250mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mounting Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	2


KEYSTONE STOCKLIST

	Figure 990	102 (EPDM)		990300102WM4B00	300mm (1") Keystone Figure 990 Resilient Seated Butterfly Valve, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, EPDM Seat, Stainless Steel Shaft, Wafer Mull Drilling PN6/10/16/ANSI 150 & Table E.; Baresha	2
	Figure 990	106 (NBR)		990025106WM4B00	25mm (1") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Mull Drilling PN10/16/ANSI 150, Bare Shaft End	15
	Figure 990	106 (NBR)		990040106WM4B00	40mm (1 1/2") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Mull Drilling PN10/16/ANSI 150, Bare Shaft End	11
	Figure 990	106 (NBR)		990050106WM4B00	50mm (2") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Mull Drilling PN10/16/ANSI 150, Bare Shaft End	2
	Figure 990	106 (NBR)		990065106WM4B00	65mm (2 1/2") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Mull Drilling PN10/16/ANSI 150, Bare Shaft End	2

KEYSTONE STOCKLIST

	Figure 990	106 (NBR)		990080106WM4B00	80mm (3") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Muller Drilling PN10/16/ANSI 150, Bare Shaft End	2
	Figure 990	106 (NBR)		990100106WM4B00	100mm (4") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Muller Drilling PN10/16/ANSI 150, Bare Shaft End	5
	Figure 990	106 (NBR)		990125106WM4B00	125mm (5") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Muller Drilling PN10/16/ANSI 150, Bare Shaft End	4
	Figure 990	106 (NBR)		990150106WM4B00	150mm (6") Keystone Figure 990 Butterfly Valve, Trim 106, Cast Iron EN-GJL-250 Body, Stainless Steel EN-1.4408 Disc, NBR Seat, Stainless Steel Shaft, Wafer Muller Drilling PN10/16/ANSI 150, Bare Shaft End	6
	Figure 990	005 (PTFE/EPDM)		990050005WM4B00	50mm (2") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Muller Drilling PN10/16/ANSI 150, Bare Shaft End	16

KEYSTONE STOCKLIST

	Figure 990	005 (PTFE/EPDM)		990065005WM4B00	65mm (2 1/2") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Mul Drilling PN10/16/ANSI 150, Bare Shaft End	9
	Figure 990	005 (PTFE/EPDM)		990080005WM4B00	80mm (3") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Mul Drilling PN10/16/ANSI 150, Bare Shaft End	14
	Figure 990	005 (PTFE/EPDM)		990100005WM4B00	100mm (4") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Mul Drilling PN10/16/ANSI 150, Bare Shaft End	24
	Figure 990	005 (PTFE/EPDM)		990125005WM4B00	125mm (5") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Mul Drilling PN10/16/ANSI 150, Bare Shaft End	3
	Figure 990	005 (PTFE/EPDM)		990150005WM4B00	150mm (6") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Mul Drilling PN10/16/ANSI 150, Bare Shaft End	17

KEYSTONE STOCKLIST

	Figure 990	005 (PTFE/EPDM)		990200005WM4B00	200mm (8") Keystone Figure 990 Butterfly Valve, Trim 005, Cast Iron Epoxy Coated White Body, Stainless Steel 316 Disc, Stainless Steel 316 Shaft, PTFE / EPDM Seat, Wafer Mul Drillling PN10/16/ANSI 150, Bare Shaft End	11
	Figure 990	102 (EPDM)		93AB39	ISV-1006683 : SEAT;;F099;DN25 / NPS 1;EPDM - FG;STD	5
	Figure 990	102 (EPDM)		26DF89	ISV-1006684 : SEAT;;FIG 099;DN 40 / NPS 1.5;EPDM;STD 533G GALLO	3
	F990 Spares	102 (EPDM)		ISV-1006684	ISV-1006684 - 40mm (1 1/2") EPDM (HT) Seat To Suit F990 Butterfly Valve	5
	F990 Spares	102 (EPDM)		ISV-1006641	ISV-1006641 - 50mm (2") EPDM (HT) Seat To Suit F990 Butterfly Valve	2

KEYSTONE STOCKLIST

	F990 Spares	102 (EPDM)		ISV-1006645	ISV-1006645 - 65mm (2 1/2") EPDM (HT) Seat To Suit F990 Butterfly Valve	2
	F990 Spares	102 (EPDM)		ISV-1006647	ISV-1006647 - 80mm (3") EPDM (HT) Seat To Suit F990 Butterfly Valve	2
	F990 Spares	102 (EPDM)		ISV-1006643	ISV-1006643 - 100mm (4") EPDM (HT) Seat To Suit F990 Butterfly Valve	10
	F990 Spares	102 (EPDM)		ISV-1006642	ISV-1006642 - 150mm (6") EPDM (HT) Seat To Suit F990 Butterfly Valve	3
	F990 Spares	102 (EPDM)		ISV-1006644	ISV-1006644 - 200mm (8") EPDM (HT) Seat To Suit F990 Butterfly Valve	5

KEYSTONE STOCKLIST

	F990 Spares	102 (EPDM)		ISV-1006640	ISV-1006640 - 250mm (10") EPDM (HT) Seat To Suit F990 Butterfly Valve	6
	F990 Spares	102 (EPDM)		ISV-1006648	ISV-1006648 - 300mm (12") EPDM (HT) Seat To Suit F990 Butterfly Valve	2
	F990 Spares	106 (NBR)		ISV-1342238	25mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	106 (NBR)		ISV-1006470	40mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	106 (NBR)		ISV-1342217	50mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	10

KEYSTONE STOCKLIST

	F990 Spares	106 (NBR)		ISV-1342201	65mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	106 (NBR)		ISV-1006473	80mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	106 (NBR)		ISV-1006474	100mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	20
	F990 Spares	106 (NBR)		ISV-1342203	125mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	15
	F990 Spares	106 (NBR)		ISV-1342218	150mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	10

KEYSTONE STOCKLIST

	F990 Spares	106 (NBR)		ISV-1342204	200mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	10
	F990 Spares	106 (NBR)		ISV-1342250	250mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	106 (NBR)		ISV-1006479	300mm NBR (BUNA-FG) Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	005 (PTFE/EPDM)		ISV-1006540	SEAT;F999;DN 50 / NPS 2;PTFE / EPDM	9
	F990 Spares	005 (PTFE/EPDM)		ISV-1006541	SEAT;F999;DN 65 / NPS 2.5;PTFE / EPDM	9

KEYSTONE STOCKLIST

	F990 Spares	005 (PTFE/EPDM)		ISV-1006542	SEAT;F999;DN 80 / NPS 3;PTFE / EPDM	9
	F990 Spares	005 (PTFE/EPDM)		ISV-1006543	SEAT;F999;DN 100 / NPS 4;PTFE / EPDM	12
	F990 Spares	005 (PTFE/EPDM)		ISV-1006544	125mm F990 PTFE / EPDM Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	005 (PTFE/EPDM)		ISV-1006545	SEAT;F999;DN 150 / NPS 6;PTFE / EPDM	3
	F990 Spares	005 (PTFE/EPDM)		ISV-1006546	SEAT;F999;DN 200 / NPS 8;PTFE / EPDM	3

KEYSTONE STOCKLIST

	F990 Spares	005 (PTFE/EPDM)		ISV-1006547	250mm F990 PTFE / EPDM Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	005 (PTFE/EPDM)		ISV-1006548	300mm F990 PTFE / EPDM Seat to Suit Keystone Figure 990 Butterfly Valve	2
	F990 Spares	All models		ISV-1006504	BUSHING;;F099;DN 25 / NPS 1;ACETAL TP;STD;UPPER;	5
	F990 Spares	All models		ISV-1145262	ISV-1145262:Ring;Quad;;9.20 x 2.62;NBR;;	5
	F990 Spares	All models		ISV-1006427	50 & 80mm Stem Packing - F100 - NPS 2 - NBR Std - to suit F990 Legacy Codes: Oracle: 89TT43; SAP: 11050819	13

KEYSTONE STOCKLIST

	F990 Spares	All models		ISV-1006505	Stem Bushing to suit Keystone 2" - 3" F990 Legacy Codes: Oracle: 26EJ71; SAP: 11268700	13
	F990 Spares	All models		ISV-1006428	100mm Stem Packing - F100 - NPS 2 - NBR Std - to suit F990 Legacy Codes: Oracle: 15KC40; SAP: 11052102	12
	F990 Spares	All models		ISV-1006506	Stem Bushing to suit 4" F990 Legacy Codes: Oracle: 57AV69; SAP: 11268656	12
	F990 Spares	All models		ISV-1006429	125 & 150mm Stem Packing - F100 - NPS 2 - NBR Std - to suit F990 Legacy Codes: Oracle: 74KM82; SAP: 11050884	11
	F990 Spares	All models		ISV-1006507	Stem Bushing to suit 5 & 6" F990 Legacy Codes: Oracle: 37CU84; SAP: 11268672	11






KEYSTONE STOCKLIST

	F990 Spares	All models		ISV-1006430	200mm Stem Packing - F100 - NPS 2 - NBR Std - to suit F990 Legacy Codes: Oracle: 69LE25; SAP: 11239896	12
	F990 Spares	All models		ISV-1006508	Stem Bushing to suit 8" F990 Legacy Codes: Oracle: 98AX33; SAP: 11268674	12
	F990 Spares	All models		ISV-1006431	250 & 300mm Stem Packing - F100 - NPS 2 - NBR Std - to suit F990 Legacy Codes: Oracle: 71YM34; SAP: 11050756	11
	F990 Spares	All models		ISV-1006509	Stem Bushing to suit 10 & 12" F990 Legacy Codes: Oracle: 88GK32; SAP: 11268694	10
	Figure 320	112 (EPDM)		320050112HM1B00	50mm (2") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Multidrilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	6



KEYSTONE STOCKLIST

	Figure 320	112 (EPDM)		320065112HM1B00	65mm (2.1/2") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	2
	Figure 320	112 (EPDM)		320080112HM1B00	80mm (3") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	4
	Figure 320	112 (EPDM)		320100112HM1B00	100mm (4") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	3
	Figure 320	112 (EPDM)		320125112HM1B00	125mm (5") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	2
	Figure 320	112 (EPDM)		320150112HM1B00	150mm (6") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bare Shaft	4






KEYSTONE STOCKLIST

	Figure 320	112 (EPDM)		320200112HM1B00	200mm (8") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	4
	Figure 320	112 (EPDM)		320250112HM1B00	250mm (10") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	3
	Figure 320	112 (EPDM)		320300112HM1B00	300mm (12") Keystone Figure 320 Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, EPDM Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bare Shaft	1
	Figure 320	116 (NBR)		320050116HM1B00	50mm (2") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	5
	Figure 320	116 (NBR)		320065116HM1B00	65mm (2.1/2") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	5






KEYSTONE STOCKLIST

	Figure 320	116 (NBR)		320080116HM1B00	80mm (3") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	5
	Figure 320	116 (NBR)		320100116HM1B00	100mm (4") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	5
	Figure 320	116 (NBR)		320125116HM1B00	125mm (5") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	6
	Figure 320	116 (NBR)		320150116HM1B00	150mm (6") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	6
	Figure 320	116 (NBR)		320200116HM1B00	200mm (8") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft	5






KEYSTONE STOCKLIST

	Figure 320	116 (NBR)		320250116HM1B00	250mm (10") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	3
	Figure 320	116 (NBR)		320300116HM1B00	300mm (12") Keystone Figure 320 Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150, MPWP 16 Bar, Bareshaft.	1
	GR Series	112 (EPDM)	Wafer	GRB025112WMDB00	25mm (1") Keystone Series GRB Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	3
	GR Series	112 (EPDM)	Wafer	GRB032112WMDB00	32mm (1 1/4") Keystone Series GRB Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	3
	GR Series	112 (EPDM)	Wafer	GRB040112WMDB00	40mm (1. 1/2") Keystone Series GRB Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	3






KEYSTONE STOCKLIST

	GR Series	112 (EPDM)	Wafer	GRW050112WMDB00	50mm (2") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	10
	GR Series	112 (EPDM)	Wafer	GRW065112WMDB00	65mm (2.1/2") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, 431 Stainless Steel STEM, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	2
	GR Series	112 (EPDM)	Wafer	GRW080112WMDB00	80mm (3") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	6
	GR Series	112 (EPDM)	Wafer	GRW100112WMDB00	100mm (4") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	6
	GR Series	112 (EPDM)	Wafer	GRW125112WMDB00	125mm (5") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	2

KEYSTONE STOCKLIST

	GR Series	112 (EPDM)	Wafer	GRW150112WMDB00	150mm (6") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	4
	GR Series	112 (EPDM)	Wafer	GRW200112WMDB00	200mm (8") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	12
	GR Series	112 (EPDM)	Wafer	GRW250112WMDB00	250mm (10") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	3
	GR Series	112 (EPDM)	Wafer	GRW300112WMDB00	300mm (12") Keystone Series GRW Trim 112, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, High Temp EPDM Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	2
	GR Series	116 (NBR)	Wafer	GRW050116WMDB00	50mm (2") Keystone Series GRW Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Mult-Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	4




KEYSTONE STOCKLIST

	GR Series	116 (NBR)	Wafer	GRW080116WMDB00	80mm (3") Keystone Series GRW Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	5
	GR Series	116 (NBR)	Wafer	GRW100116WMDB00	100mm (4") Keystone Series GRW Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	5
	GR Series	116 (NBR)	Wafer	GRW125116WMDB00	125mm (5") Keystone Series GRW Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR - FG Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	2
	GR Series	116 (NBR)	Wafer	GRW150116WMDB00	150mm (6") Keystone Series GRW Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR-FG Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E/JIS 10, MPWP 16 Bar, Bare Shaft.	8
	GR Series	116 (NBR)	Wafer	GRW200116WMDB00	200mm (8") Keystone Series GRW Trim 116, Resilient Seated Butterfly Valve, Ductile Iron Body, 316 Stainless Steel Disc, Stainless Steel Shaft, NBR Liner, Wafer Pattern Multidirectional Drilled PN10/16/ANSI#150/BS10E, MPWP 16 Bar, Bare Shaft.	3

KEYSTONE STOCKLIST

	GR Series	112 (EPDM)	Lugged	GRL040112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 40mm / 1 1/2"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	2
	GR Series	112 (EPDM)	Lugged	GRL050112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 50mm / 2"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	1
	GR Series	112 (EPDM)	Lugged	GRL065112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 65mm / 2 1/2"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	2
	GR Series	112 (EPDM)	Lugged	GRL080112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 80mm / 3"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	1
	GR Series	112 (EPDM)	Lugged	GRL100112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 100mm / 4"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	1

KEYSTONE STOCKLIST

	GR Series	112 (EPDM)	Lugged	GRL125112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 125mm / 5"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	2
	GR Series	112 (EPDM)	Lugged	GRL150112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 150mm / 6"; Lugged; Drilling: PN 10/16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	2
	GR Series	112 (EPDM)	Lugged	GRL200112L10B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 200mm / 8"; Lugged; Drilling: PN 10; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	1
	GR Series	112 (EPDM)	Lugged	GRL200112L16B00	Keystone Series GR Resilient Seated Butterfly Valve Model: Series GR; Size: 200mm / 8"; Lugged; Drilling: PN 16; Body: Ductile Iron; Disc: Stainless Steel 316; Stem: Stainless Steel 431; Seat: EPDM - FG HT; Mounting: ISO 5211; Baresha	1
	89 Series	E (ISO)	Double Acting	89E003Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-003, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD16x11	14

KEYSTONE STOCKLIST

	89 Series	E (ISO)	Single Acting (Fail Close)	89E003Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-003, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD16x11	3
	89 Series	E (ISO)	Double Acting	89E004Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-004, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD16x11	8
	89 Series	E (ISO)	Single Acting (Fail Close)	89E004Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-004, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD16x11	12
	89 Series	E (ISO)	Double Acting	89E006Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-006, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD20x14	12
	89 Series	E (ISO)	Single Acting (Fail Close)	89E006Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-006, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD20x14	9

KEYSTONE STOCKLIST

	89 Series	E (ISO)	Double Acting	89E009Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-009, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: DD20x14	7
	89 Series	E (ISO)	Single Acting (Fail Close)	89E009Q3SA0PM00	Keystone Pneumatic Actuator, Fig 89E-009, Spring to Close (CW), 10 Springs, 1/4" BSPP Air Ports, Standard Temp., NBR Seals, Dual Travel Stops (Open+Close), Metric Threading, Standard Version, Flange: F05+F07 (ISO5211), Drive: DD20x14	8
	89 Series	E (ISO)	Double Acting	89E014Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-014, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F07 (ISO5211), Drive: DD20x14	2
	89 Series	E (ISO)	Single Acting (Fail Close)	89E014Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-014, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F07 (ISO5211), Drive: DD20x14	8
	89 Series	E (ISO)	Double Acting	89E020Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-020, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F07+F10+F12 (ISO5211), Drive: DD25x18	3

KEYSTONE STOCKLIST

	89 Series	E (ISO)	Single Acting (Fail Close)	89E020Q3SA0PM00	Keystone Pneumatic Actuator, Fig 89E-020, Spring to Close (CW), 10 Springs, 1/4" BSPP Air Ports, Standard Temp., NBR Seals, Dual Travel Stops (Open+Close), Metric Threading, Standard Version, Flange: F07+F10+F12 (ISO5211), Drive: DD25x18	9
	89 Series	E (ISO)	Double Acting	89E032Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-032, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F10+F12 (ISO5211), Drive: 35K10x8	1
	89 Series	E (ISO)	Single Acting (Fail Close)	89E032Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-032, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F10+F12 (ISO5211), Drive: 35K10x8	10
	89 Series	E (ISO)	Double Acting	89E052Q1XX0PM00	89E-05201XXP14N2MM12M35 Keystone pneumatic actuator, Fig 89E-052, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F10+F12 (ISO5211), Drive: 35K10x8	2
	89 Series	E (ISO)	Single Acting (Fail Close)	89E052Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-052, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F10+F12 (ISO5211), Drive: 35K10x8	3

KEYSTONE STOCKLIST

	89 Series	E (ISO)	Double Acting	89E085Q1XX0PM00	Keystone pneumatic actuator, Fig 89E-085, Double acting, no springs, 1/4" BSPP air ports, Standard temp, NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: PCD F12+F16 (ISO5211), Drive: 50K14x9	1
	89 Series	E (ISO)	Single Acting (Fail Close)	89E085Q3SA0PM00	Keystone pneumatic actuator, Fig 89E-085, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F12+F16 (ISO5211), Drive: 50K14x9	1
	89 Series	U (Non ISO)	Double Acting	89U003Q1XX0PM00	Keystone pneumatic actuator, Fig 89U-003, Double acting, no springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version New Part No. 89U-00301XXP14N2MC34P09	34
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U003Q3SA0PM00	Keystone pneumatic actuator, Fig 89U-003, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version	3
	89 Series	U (Non ISO)	Double Acting	89U004Q1XX0PM00	Keystone Pneumatic Actuator, Figure 89U, Size 004, Double Acting, 1/4" BSPP Air Connections, Standard Service, Dual Travel Stops (Open + Close), Metric Threading, Standard Version, Flange PCD 82.5, Drive DD 15.88 x 11.1mm	2

KEYSTONE STOCKLIST

	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U004Q3SA0PM00	Keystone pneumatic actuator, Fig 89U-004, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version	2
	89 Series	U (Non ISO)	Double Acting	89U006Q1XX0PM00	Keystone Pneumatic Actuator Fig 89U-006 DA, Double Acting, No Springs 1/4" BSPP Air Ports Standard Temperature NBR Seals Dual Travel Stops (Open + Close) Metric Threading, Standard Version Flange PCD 82,5 Drive DD 19.05 x 12.7 mm	5
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U006Q3SA0PM00	Keystone pneumatic actuator, Fig 89U-006, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: PCD 3.25", Drive: 19.05x12.7 mm	4
	89 Series	U (Non ISO)	Double Acting	89U009Q1XX0PM00	Keystone Pneumatic Actuator (PQU) Double Acting, No Springs, 1/4" BSPP Air Ports, Standard Temperature, NBR Seals, Dual Travel Stops (Open + Close), Metric Threading, Standard Version, Flange PCD 82.5 (Keystone 45 Degrees).	2
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U009Q3SA0PM00	Keystone pneumatic actuator, Fig 89U-009, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: PCD 82.5 + 127mm, Drive: 19.05 x 12.7mm	2

KEYSTONE STOCKLIST

	89 Series	U (Non ISO)	Double Acting	89U014Q1XX0PM00	Keystone Pneumatic Actuator (PQU) 89U-014 Double Acting, No Springs, 1/4" BSPP Air Ports, Standard Temperature, NBR Seals, Dual Travel Stops (Open + Close), Metric Threading, Standard Version, Flange: PCD 82.5 + 127mm, Drive: 19.05 x 12.7mm	3
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U014Q3SA0PM00	Keystone pneumatic actuator, Fig 89U-014, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: PCD 82.5 + 127mm, Drive: 19.05 x 12.7mm	2
	89 Series	U (Non ISO)	Double Acting	89U020Q1XX0PM00	Keystone Pneumatic Actuator, Figure 89U, Size 020, Double Acting, 1/4" BSPP Air Connections, High Temperature Service, Dual Travel Stops (Open + Close), Metric Threading, Standard Version. PCD 3.25+5.00", Drive: DD 22.2x15.88 mm	3
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U020Q3SA0PM00	Keystone Pneumatic Actuator, Fig 89U-020, Spring to Close (CW), 10 Springs, 1/4" BSPP Air Ports, Standard Temp., NBR Seals, Dual Travel Stops (Open+Close), Metric Threading, Flange: PCD 3.25+5.00", Drive: DD 22.2x15.88 mm	2
	89 Series	U (Non ISO)	Double Acting	89U032Q1XX0PM00	Keystone Figure 89 Pneumatic Quarter Turn Actuator, Model F89, Size: 032, Double Acting, Air Connection: 1/4" BSPP, Temperature Service: Standard, 2 x Travel Stops, Dual Shaft (std), Flange Threading: Metric, Operator Mounting Flange, PCD 3.25+5.00" (Keystone 45 degrees) Shaft / Stem Connection: DD 7/8" x 5/8" (22.2 x 15.88 mm)	2

KEYSTONE STOCKLIST

	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U032Q3SA0PM00	Keystone Pneumatic Actuator, Quarter-turn, Model F89U-032-FC Spring to Close (CW) 10 springs, 1/4" NPT air ports, NBR (std) seals, dual travel stops (open+close), Flange: PCD 3.25+5.00"; Drive: 22.2x15.88 mm	1
	89 Series	U (Non ISO)	Double Acting	89U051Q1XX0PM00	Keystone Figure 89 Pneumatic Quarter Turn Actuator, Model F89, Size: 051, Double Acting, Air Connection: 1/4" BSPP, Temperature Service: Standard, 2 x Travel Stops, Dual Shaft (std), Flange Threading: Metric, Operator Mounting Flange, PCD 3.25+5.00" (Keystone 45 degrees) Shaft / Stem Connection: DD 1-1/8" x K1/4x1/4" (28.6 x K6.35 mm)	2
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U051Q3SA0PM00	Keystone pneumatic actuator, Fig 89U-051, Spring to close (CW), 10 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: PCD 3.25+5.00", Drive: Bore 28.6K6.35 mm	2
	89 Series	U (Non ISO)	Double Acting	89U085Q1XX0PM00	Keystone Figure 89 Pneumatic Quarter Turn Actuator, Model F89, Size: 085, Double Acting, Air Connection: 1/4" BSPP, Temperature Service: Standard, 2 x Travel Stops, Dual Shaft (std), Flange Threading: Metric, Operator Mounting Flange, PCD 5.00+6.500" (Keystone 45 degrees) Shaft / Stem Connection: DD 1-5/8" x K3/8x3/8" (41.3 x K9.53 mm)	2
	89 Series	U (Non ISO)	Single Acting (Fail Close)	89U085Q3SA0PM00	Keystone Pneumatic Actuator, Fig 89U-085, Spring to Close (CW), 10 Springs, 1/4" BSPP Air Ports, Standard Temp, NBR Seals, Dual Travel Stops (Open+Close), Metric Threading, Standard Version, Flange: PCD 127mm & 165mm, Drive: Bore 41.3K9.53 mm	2






KEYSTONE STOCKLIST

	89 Series	D (Star Drive)	Double Acting	89D003Q1XX0PM00	Keystone Pneumatic Actuator, Fig 89D-003, Double Acting, No Springs, 1/4" BSPP Air Ports, Standard Temp., NBR Seals, Dual Travel Stops (Open+Close), Metric Threading, Standard Version, Flange: F05+F07 (ISO5211), Drive: Star 14	5
	89 Series	D (Star Drive)	Single Acting (Fail Close)	89D003Q3S80PM00	Keystone pneumatic actuator, Fig 89D-003, Spring to close (CW), 08 springs, 1/4" BSPP air ports, Standard temp, NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: Star14	4
	89 Series	D (Star Drive)	Single Acting (Fail Close)	89D004Q3S80PM00	Keystone pneumatic actuator, Fig 89D-004, Spring to close (CW), 08 springs, 1/4" BSPP air ports, Standard temp, NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: Star14	14
	89 Series	D (Star Drive)	Single Acting (Fail Close)	89D006Q3S80PM00	Keystone pneumatic actuator, Fig 89D-006, Spring to close (CW), 08 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: Star17	16
	89 Series	D (Star Drive)	Single Acting (Fail Close)	89D009Q3S80PM00	Keystone pneumatic actuator, Fig 89D-009, Spring to close (CW), 08 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F05+F07 (ISO5211), Drive: Star17	14






KEYSTONE STOCKLIST

	89 Series	D (Star Drive)	Single Acting (Fail Close)	89D014Q3S80PM00	Keystone pneumatic actuator, Fig 89D-014, Spring to close (CW), 08 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F07 (ISO5211), Drive: Star17	4
	89 Series	D (Star Drive)	Single Acting (Fail Close)	89D052Q3S80PM00	Keystone pneumatic actuator, Fig 89D-052, Spring to close (CW), 08 springs, 1/4" BSPP air ports, Standard temp., NBR seals, dual travel stops (open+close), Metric threading, Standard version, Flange: F10+F12 (ISO5211), Drive: Star27	2
	Electric Act	KPE (ISO)		KPE063HVPD002E3	Keystone KPE063HVPD002E3 Actuator ELECTRIC ACTUATOR;Keystone EPI2 Metric;063; High Voltage; Single Phase 100-240 V AC/DC;15-28-48 secs S3-100%;none;WP-IP68;Ø 20, DD14.	1
	Electric Act	KPE (ISO)		KPE125HVPD002E5	Keystone KPE125HVPD002E5 Actuator ELECTRIC ACTUATOR;Keystone EPI2 Metric;125; High Voltage; Single Phase 100-240 V AC/DC;15-28-48 secs S3-100%;none;WP-IP68;Ø 30, DD22.	3
	Electric Act	NA		KPXXXXXXXXP1XXX	OM1 4-20mA Card for a Keystone EPI-2 actuator (All sizes), PCB module 1 for AO/AI Positioner & Retransmission 4-20mA or 0-10V=, Monitor Relay, 4 Extra Contacts SPST, Blinker Facility and TVCRM-0094-EN included.	1

KEYSTONE STOCKLIST

	Premiair Spares			ISV-1192839	ISV-1192839:SPARES KIT (NITRILE) 002 GLASGOW REF : 91CB61 COMPRISING :- 2 OFF ENDCAP `O`RINGS 2 OFF PISTON `O`RINGS 2 OFF AIR CONNECTOR `O`RINGS 1 OFF SHAFT TOP `O`RING 1 OFF SHAFT BOTTOM `O`RING 1 OFF BASEPLATE `O`RING 1 OFF SHAFT TOP BEARING 1 OFF SHAFT BOTTOM BEARING 1 OFF SHAFT TOP SPACER 1 OFF SHAFT BOTTOM SPACER 2 OFF PISTON BACKING PAD 2 OFF PISTON SUPPORT RING 2 OFF TRAVEL STOP O-RINGS	2
	Premiair Spares			ISV-1192840	ISV-1192840:SPARES KIT (NITRILE) 004 P/N PR3925006ML18 11097225 11137927	2
	Premiair Spares			ISV-1192843	ISV-1192843:SPARES KIT (NITRILE) 009 GLASGOW REF : 39YU57 COMPRISING :- 2 OFF ENDCAP `O`RINGS 2 OFF PISTON `O`RINGS 2 OFF AIR CONNECTOR `O`RINGS 1 OFF SHAFT TOP `O`RING 1 OFF SHAFT BOTTOM `O`RING 1 OFF BASEPLATE `O`RING 1 OFF SHAFT TOP BEARING 1 OFF SHAFT BOTTOM BEARING 1 OFF SHAFT TOP SPACER 1 OFF SHAFT BOTTOM SPACER 2 OFF PISTON BACKING 2 OFF PISTON SUPPORT RING 2 OFF TRAVEL STOP `O`RINGS	5
	79 Act Spares			ISV-1106501	ISV-1106501 - Repair Kit 79U 024 Buna with Grease	5
	79 Act Spares			ISV-1107716	ISV-1107716 - Repair Kit 79U 036 Buna with Grease	5

KEYSTONE STOCKLIST

	79 Act Spares			ISV-1102854	ISV-1102854 - Spares Kit to suit Keystone 79U/E/D - 065/066 - Nitrile O-Rings	3
	79 Act Spares			ISV-1227139	ISV-1227139 - Repair Kit 79U 0090 Buna with Grease	2
	79 Act Spares			ISV-1145235	ISV-1145235 - Spares Kit to suit Keystone F79U/E-180/181(S) and PremiAir 180(S) Consisting of: - Top- and bottom bearings c/w NBR seals - Piston backing pads (2) and rings (2) - Piston- and E/cap O-rings (NBR) - SS internal circlip + instructions	1
	F401	Non-ISO		401050ABB00	Type 401 Lever Kit to suit F990 50mm-80mm, Non-ISO, CS/St; Double D; B14.28/D9.5; PCD 82.5	6
	F401	Non-ISO		401050ACB00	Type 401 Lever Kit to suit F990 100mm, Non-ISO, CS/St; Double D; B15.88/DD11.1; PCD 82.5	3






KEYSTONE STOCKLIST

	F401	Non-ISO		401060ADB00	Type 401 Lever Kit to suit F990 125mm-150mm, Non-ISO, CS/St; Double D; B19.05/DD12.7; PCD 82.5	6
	F401	Non-ISO		401040AEC00	Type 401 Lever Kit to suit F990 200mm, Non-ISO, DI/SS; Double D; B22.2/DD15.88; PCD 127	13
	F410	Non-ISO	Lockable	ISV-1146381	25mm-40mm Type 410 Composite Non-ISO Lockable Lever, Double D to suit Fig. 990	33
	F410	Non-ISO	Lockable	ISV-1146382	50mm-80mm Type 410 Composite Non-ISO Lockable Lever, Double D to suit Fig. 990	3
	F410	Non-ISO	Lockable	ISV-1146384	100mm Type 410 Composite Non-ISO Lockable Lever, Double D to suit Fig. 990	3

KEYSTONE STOCKLIST

	F410	Non-ISO	Lockable	ISV-1146386	125mm-150mm Type 410 Composite Non-ISO Lockable Lever, Double D to suit Fig. 990	5
	F419	ISO	Lockable	419CS0AMD00	Lever Kit, Composite, SS, Double D, Bore 12mm/DD 8mm, F05 Mounting (419CS0AMD00)	20
	F419	ISO	Lockable	419CS0ANE00	Lever Kit, Composite, SS, Double D, Bore 16mm/DD 11mm, F07 Mounting (419CS0ANE00)	27
	F419	ISO	Lockable	419CS0APE00	Lever Kit, Composite, SS, Double D, Bore 20mm/DD 14mm, F07 Mounting (419CS0APE00)	21
	F412	ISO		412040AQESC	Lever to suit F320 - 200mm Ductile Iron	2

KEYSTONE STOCKLIST

	F422	Non-ISO		CUC30300FAFAC01	ISV-1173132: Gear kit Fig. 422 CU 030, handwheel Ø300, hand wheel shaft: 304 SS, shaft hole: Ø28,6 mm, two keyways for key: 6,4x6,4 mm, PCD:127mm, RAL 9005 (black), Indicator yellow with black arrow	7
	F455	ISO		CMC24150FAP0701	G/Box c/w Handwheel, Ductile Iron 65 - 100mm Adaptor No. MABSE30E2000E00 125mm - 150mm - Direct Mount - No adaptor required 200mm - Adaptor No. MABSU70E3000E00	6
	F455	ISO		CMC30300MAR1201	Gear Kit F455 ISO CM 030 with Handwheel Ø300 Handwheel Shaft: SS Metric Threads: Shaft Hole Ø30 DD22, F07/F010/F12 Black RAL 9005, Indicator Yellow with Black Arrow. Padlocking Flanges 200mm - 250mm - 300mm - Direct Mount - No adaptor required	7
	Asco Solenoid			791A024DWD1MN00	Solenoid Operated Valve Keystone 791A; 3/2-5/2 Way, NAMUR Footprint, Single Coil, Hard Anodised Aluminium Body with Air Supply G1/4", Manual Override by Screw (Latching), Pilot Operated Air Pressure: 2.8...8.3 bar, 24 V DC Supply, IP65 Coil Housing (P=1,6 W), Electric Connection: Standard Plug Connector to EN 175301-803 form A- Pg11 Cable Gland for Cable with an Outer Diameter from 6 to 10 mm. Temperature range: - 25°C to +60°C	5
	Norgren Solenoid			791N024DWD1MN30	Solenoid Operated Valve AVID 791N; 3/2-5/2 Way, NAMUR Footprint, Hard Anodised Aluminium Body with Air Supply G1/4", Manual Override, Pilot Operated (Direct Acting), 24V DC Supply, IP65 Coil Housing (P=1,7 W), Electric Connection: Standard Plug Connector to EN 175301-803 c/w M16x1.5 Cable Gland; incl. Plug	70

KEYSTONE STOCKLIST