
Toothed belt axes ELGC-TB-KF





This drive is also available as a product unit as part of the Simplified Motion Series: Toothed belt axis ELGS-TB-KF



Key features

At a glance

- Optimal installation space to working space ratio
- Protected against external influences by internal guide
- Compact, integrated coupling, easy to service
- Unique assembly system
- · Compact double bearing integrated in the axis to save space
- · Stainless steel cover strip kept in place with magnetic strips
- · Easy to clean and less susceptible to contamination

Compact

Flexible

Optimum dimensions thanks to the integrated compact coupling and a very short slide Adapterless combination of ELGC and EGSC using the innovative "one size down" assembly system

Integrated

Simple position sensing with proximity switch SMT-8M and integrated positioning magnet

Protected

The cover strip and optional vacuum connection protect against particle emissions and atmospheric pollution

Modular and flexible with motor, motor mounting kit and servo drive





Stepper motor

Servo drive Servo drive

Motor controller for stepper motor





Motor mounting kit

Axial kit

Simplicity in one unit

This product is also available as a product unit as part of the Simplified Motion Series:



- The Simplified Motion Series combines the simplicity of pneumatics with the benefits of electric automation. The perfect solution for all users who are looking for an electric alternative for very simple movement and positioning tasks, but don't want the commissioning process for traditional electric drive systems that can often be quite complex.
- Simplified functionality for simple movements between two end positions
- A variety of movements with different mechanical systems
- Integrated products eliminate the need for a control cabinet
- · Quick and easy commissioning without software or special expertise
- Digital I/O and IO-Link integrated as standard

Key features

From individual axis to complete handling system • The toothed belt and spindle axes ELGC and mini slide EGSC form a scalable modular system for compact automation • The shared platform architecture creates a consistent range with matching interfaces. A large number of systems can be realised entirely without adapter plates • Powerful drive and guide components ensure a long service life, as well as excellent load capacity and reliability • The uniform and universal range of accessories reduces warehousing and design costs • Two position sensing functions can be selected: - With magneto-resistive proximity switches (detection via integrated magnets) - With inductive proximity switches (detection via switch lug) The products for the handling system Spindle axis Toothed belt axis Guide axis Mini slide ELGC-BS ELGC-TB ELFC EGSC Typical handling systems For applications where compact dimensions are essential, the axes ELGC can be combined into very space-saving handling systems that are suitable for assembly systems, test and inspection systems, small parts handling, the electronics industry and desktop applications. The very compact linear axes ELGC, mini slide EGSC and electric cylinder EPCC offer an optimal ratio between installation space and working space. They

 Cantilever system
 Planar surface gantry
 3-dimensional gantry


feature a common system approach and platform architecture and the connections are largely adapterless.

Key features


Matrix showing combinations between axis ELGC/ELGS-TB, ELGC/ELGS-BS, mini slide EGSC/EGSS-BS, electric cylinder EPCC/EPCS-BS and guide axis ELFC Mounting options with profile mounting and via angle kit


		Assembly axis ELGC-BS/-TB; ELFC; EGSC-BS; EPCC-BS; ELGS-BS/-TB; EGSS-BS, EPCS-BS				
	Size	25	32	45	60	
Base axis	32		-	-	-	
ELGC-BS/-TB; ELFC;	45	-		-	-	
ELGS-BS/-TB	60	-	-		-	
	80	-	-	-		

With profile mounting EAHF-L2-...-P-D...



• Mounting option: base axis with one-size-down assembly axis







With angle kit EHAA-D-L2-...-AP



 Mounting option: base axis rotated through 90° with one-size-down assembly axis






Matrix showing combinations between axis ELGC/ELGS-TB, ELGC/ELGS-BS, mini slide EGSC/EGSS-BS, electric cylinder EPCC/EPCS-BS and guide axis ELFC Assembly options with adapter kit or direct mounting


			axis ELGC-I TB; EGSS-B			; EPCC-BS;
	Size	25	32	45	60	80
Base axis	32		•	-	-	-
ELGC-BS/-TB; ELFC;	45	-	-		-	-
ELGS-BS/-TB	60	-	-			-
	80	-	-	-		


With adapter kit EHAA-D-L2

- Mounting option: base axis with the same size assembly axis
- Mounting option: base axis with height adjustment for one-size-down assembly axis
- When motors are mounted using parallel kits, this may lead to interfering contours. In this case, the adapter plate is required for height compensation










With direct mounting

• Mounting option: base axis with the same size assembly axis




Type codes

001	Series
ELGC	Gantry axis
002	Drive system
ТВ	Toothed belt
003	Guide
KF	Recirculating ball bearing guide
004	Size
45	45
60	60
80	80

005	Stroke	
200	200	
300	300	
500	500	
600	600	
800	800	
1000	1000	
1200	1200	
1500	1500	
1800	1800	
2000	2000	

Peripherals overview



Peripherals overview

Acces	ccessories					
	Туре	Description	→ Page/Internet			
[1]	Centring pin/sleeve ZBS/ZBH	For centring loads and attachments on the slide	26			
[2]	Adapter kit EHAA-D-L2	 For axis/axis mounting with adapter plate Mounting option: base axis with same size or one-size-down assembly axis (→ page 4) When motors are mounted using parallel kits, this may lead to interfering contours. In this case, the adapter plate is required for height compensation (download CAD data → www.festo.com) 	23			
[3]	Profile mounting EAHF-L2P-D	 For axis/axis mounting without adapter plate Mounting option: base axis with one-size-down assembly axis (→ page 4) 	22			
[4]	Angle kit EHAA-D-L2AP	For mounting one-size-down vertical axes (assembly axes) on base axes with mounting position "slide at top" (→ page 4)	24			
[5]	Clamping element EADT-S-L5-32	Tool for retensioning the cover strip	26			
[6]	Sensor bracket EAPM-L2-SH	For mounting the proximity switches on the axis. The proximity switches can only be mounted using the sensor bracket	25			
[7]	Proximity switches SIES-8M	Inductive proximity switches, for T-slot	26			
	Proximity switches SMT-8M	Magnetic proximity switches, for T-slot	26			
8]	Switch lug EAPM-L2SHS	For sensing the slide position in conjunction with inductive proximity sensors SIES-8M	25			
9]	Profile mounting EAHF-L2P	For mounting the axis on the side of the profile. The profile mounting can be fixed in place on the mounting surface using the drill hole in the centre	21			
10]	Profile mounting EAHF-L2P-S	For mounting the axis on the side of the profile	20			
11]	Motor EMME-AS, EMMS-ST	Motors specially matched to the axis	19			
[12]	Axial kit EAMM-A	For axial motor mounting	19			

Sealing air connection




Air is exchanged between the interior of the cylinder and the environment via a sealing air connection. This prevents negative pressure or excess pressure arising in the interior of the cylinder.

 $\label{eq:Additional functions of the connection:} Additional functions of the connection:$

- Application of slight negative pressure prevents emission of particles
- Application of slight excess pressure prevents atmospheric pollution Suitable push-in fittings \rightarrow page 26

Data sheet









General technical data

Size		45	60	80		
Design		Electromechanical axis with toothed belt	Electromechanical axis with toothed belt			
Guide		Recirculating ball bearing guide				
Mounting position		Any				
Working stroke	[mm]	200, 300, 500, 600, 800, 1000, 1200,	200, 300, 500, 600, 800, 1000, 1200,	200, 300, 500, 600, 800, 1000, 1200,		
		1500	1500, 1800, 2000	1500, 1800, 2000		
Max. feed force F _x	[N]	75	120	250		
Max. no-load torque ¹⁾	[Nm]	0.075	0.194	0.413		
Max. no-load resistance to shifting ¹⁾	[N]	7.8	15.6	24.7		
Max. driving torque	[Nm]	0.716	1.49	4.178		
Max. speed	[m/s]	1.2	1.5	1.5		
Max. acceleration	[m/s ²]	15				
Repetition accuracy [mm]		±0.1				
Position sensing		Magneto-resistive, inductive				

1) At 0.2 m/s

Operating and environmental conditions

Operating and environmental conditions				
Ambient temperature ¹⁾	[°C]	0 +50		
Degree of protection		IP40		
Duty cycle	[%]	100		
Maintenance interval		Life-time lubrication		

1) Note operating range of proximity switches

Weight [g]

Size	45	60	80		
Basic weight with 0 mm stroke ¹⁾	760	1775	3500		
Additional weight per 10 mm stroke	23	43	73		
Moving mass	169	482	901		

1) Including slide

Toothed belt						
Size		45	60	80		
Indexing	[mm]	2	3	3		
Elongation ¹⁾	[%]	0.187	0.124	0.200		
Effective diameter	[mm]	19.1	24.83	33.42		
Feed constant	[mm/rev]	60	78	105		

1) At max. feed force

Size		45	60	80
Jo	[kg mm ²]	18.62	88.04	291.2
J _H per metre stroke	[kg mm ² /m]	2.81	8.51	19.27
J _L per kg payload	[kg mm ² /kg]	91.19	154.11	279.3

The mass moment of inertia J_A of the entire axis is calculated as follows:

 $J_A = J_O + J_H x$ working stroke [m] + $J_L x m_{payload}$ [kg]

Homing


Homing can be carried out in two ways:

- Against a fixed stop
- Using a reference switch

The following values must be observed:

Size		45	60	80
Max. impact energy	[J]	0.5x10 ⁻³	1x10 ⁻³	2x10 ⁻³
At max. homing speed	[m/s]	0.01		


Materials




Axis						
[1]	Drive cover	Painted die-cast aluminium				
[2]	Slide	Die-cast aluminium				
[3]	Cover strip	High-alloy stainless steel				
[4]	Toothed belt	Polychloroprene with glass cord and nylon coating				
[5]	Guide	Steel				
[6]	Profile	Anodised wrought aluminium alloy				
[7]	Guide pulley	Aluminium				
	Note on materials	RoHS-compliant				
		Contains paint-wetting impairment substances				

Characteristic load values

The indicated forces and torques refer to the centre of the guide. The point of application of force is the point where the centre of the guide and the longitudinal centre of the slide intersect. These values must not be exceeded during dynamic operation. Special attention must be paid to the deceleration phase.



Distance from the slide surface to the centre of the guide



Max. permissible forces and torques on the slide (strength limits)

Size		45	60	80
Fy _{max.}	[N]	300	600	900
Fz _{max.}	[N]	600	1800	2700
Mx _{max.}	[Nm]	5.5	29.1	59.8
My _{max.}	[Nm]	4.7	31.8	56.2
Mz _{max.}	[Nm]	4.7	31.8	56.2

Distance from the slide surface to the centre of the guide Size 45

Size		45	60	80
Dimension x	[mm]	42.8	54.6	72.5

Max. permissible forces and torques for the bearing calculation, for a service life of 5000 km or 5 x 10⁶ cycles

Size	-	45	60	80
Fy _{max.}	[N]	880	3641	5543
Fz _{max.}	[N]	880	3641	5543
Mx _{max.}	[Nm]	5.5	29.1	59.8
My _{max.}	[Nm]	4.7	31.8	56.2
Mz _{max.}	[Nm]	4.7	31.8	56.2

· 📲 - Note

For \bar{a} guide system to have a service life of 5000 km, the load comparison factor must have a value of fv \leq 1, based on the maximum permissible forces and torques for a service life of 5000 km.

This formula can be used to calculate a guide value.

The engineering software "PositioningDrives" is available

for more precise calculations \rightarrow www.festo.com

If the axis is subjected to two or more of the indicated forces and torques simultaneously, the following equation must be satisfied in addition to the indicated maximum loads:

Calculating the load comparison factor:

$$f_{v} = \frac{\left|F_{y1}\right|}{F_{y2}} + \frac{\left|F_{z1}\right|}{F_{z2}} + \frac{\left|M_{x1}\right|}{M_{x2}} + \frac{\left|M_{y1}\right|}{M_{y2}} + \frac{\left|M_{z1}\right|}{M_{z2}} \le 1$$

 F_1/M_1 = dynamic value F_2/M_2 = maximum value I

Calculating the service life


The service life of the guide depends on the load. To be able to make a statement as to the service life of the guide, the graph below plots the load comparison factor fv against the service life.

Load comparison factor f_v as a function of service life l

Example:

A user wants to move an x kg load. Using the formula (\rightarrow page 10) gives a value of 1.5 for the load comparison factor f_v. According to the graph, the guide would have a service life of approx. 1500 km. Reducing the acceleration reduces the Mz and My values. A load comparison factor f_v of 1 now gives a service life of 5000 km.

These values are only theoretical. You must consult your local Festo contact for a load comparison factor fv greater than 1.



Comparison of the characteristic load values for 5000 km with dynamic forces and torques of recirculating ball bearing guides

The characteristic load values of the bearing guides are standardised to ISO and JIS using dynamic and static forces and torques. These forces and torques are based on an expected service life of the guide system of 100 km according to ISO or 50 km according to JIS.

As the characteristic load values are dependent on the service life, the maximum permissible forces and torques for a 5000 km service life cannot be compared with the dynamic forces and torques of bearing guides to ISO/JIS.


To make it easier to compare the guide capacity of linear axes ELGC with bearing guides, the table below lists the theoretically permissible forces and torques for a calculated service life of 100 km. This corresponds to the dynamic forces and torques to ISO.

These 100 km values have been calculated mathematically and are only to be used for comparing with dynamic forces and torques to ISO. The drives must not be loaded with these characteristic values as this could damage the axes.


Max. permissible forces and torques for a theoretical service life of 100 km (from a guide perspective only)

Size		45	60	80
Fy _{max.}	[N]	3240	13400	20400
Fz _{max.}	[N]	3240	13400	20400
Mx _{max.}	[Nm]	20	107	220
My _{max.}	[Nm]	17	117	207
Mz _{max.}	[Nm]	17	117	207

Feed force F as a function of input torque M



Second moment of area



Size		45	60	80
ly	[mm ⁴]	140x10 ³	441x10 ³	1.37x10 ⁶
lz	[mm ⁴]	170x10 ³	542x10 ³	1.66x10 ⁶

Fy ↔

F


Data sheet

Maximum permissible support spacing L (without profile mounting) as a function of force F

In order to limit deflection in the case of large strokes, the axis may need to be supported.

The following graphs can be used to determine the maximum permissible support spacing l as a function of force F acting on the axis.

The deflection is f = 0.5 mm.



Size 60/80 2000

1750

1500

1250 Z 1000

750

500-

250

0 -

600


800

1000

1200 1400 1600

L[mm]

1800 2000




ELGC-TB-45 --- ELGC-TB-60 --- ELGC-TB-80

Recommended deflection limits

Adherence to the following deflection limits is recommended so as not to impair the functionality of the axes. Greater deformation can result in increased friction, greater wear and reduced service life.

Size	Dynamic deflection (moving load)	Static deflection (stationary load)
45 80	0.05% of the axis length, max. 0.5 mm	0.1% of the axis length

2021/06 - Subject to change





1) Coupling diameter or interference diameter of locking screw

2) Includes a stroke reserve of approx. 3 mm

Dimensions Profile			D	ownload CAD data → <u>www.festo.com</u>
Size 45	ensor bracket ng slot	Size 60		
Size	B1	В5	H9	H10
45	45	32.9	6.1	24.5
60	60	47.9	6.1	38.5
80	80	67.9	6.1	47.5

Data sheet






[5] Drill hole for centring sleeve ZBH

[6] Drill hole for centring pin ZBS

Size	B1 ±0.1	D1	D2 Ø H8		C)3	H1 ±0.1	H2 ±0.1 For D2 ±0.03
45 60	6 8	M2 M3	4			Λ4 Λ5	43.5 58	34 47
Size	L1	L2 ±0.1	L3 ±0.1	T1		T2	T3 +0.1	T4 ¹⁾
45 60	67.5 88.5	42 58	24 30	6 9		5 7	3.1 1.3	6 7.5 8.5 10

1) Recommended screw-in depth

Data sheet



Size	B1	D1	D2		D3	H1	H2
			Ø				±0.1
	±0.1		H8			±0.1	For D2 ±0.03
80	11	M4	7		M6	78	63
Size		12		T1	та	To	T4 ¹⁾
Size	L1	L2	L3	T1	T2	T3	14 -7
		±0.1	±0.1			+0.1	
80	106	73	36	12	9	1.6	11 14

1) Recommended screw-in depth

Data sheet

Ordering data

Ordering data				
	Size	Stroke	Part no.	Туре
		[mm]		
	45	200	8062768	ELGC-TB-KF-45-200
		300	8062769	ELGC-TB-KF-45-300
		500	8062770	ELGC-TB-KF-45-500
		600	8062771	ELGC-TB-KF-45-600
		800	8062772	ELGC-TB-KF-45-800
		1000	8062773	ELGC-TB-KF-45-1000
		1200	8062774	ELGC-TB-KF-45-1200
		1500	8062775	ELGC-TB-KF-45-1500
	60	200	8062776	ELGC-TB-KF-60-200
		300	8062777	ELGC-TB-KF-60-300
		500	8062778	ELGC-TB-KF-60-500
		600	8062779	ELGC-TB-KF-60-600
		800	8062780	ELGC-TB-KF-60-800
		1000	8062781	ELGC-TB-KF-60-1000
		1200	8062782	ELGC-TB-KF-60-1200
		1500	8062783	ELGC-TB-KF-60-1500
		1800	8062784	ELGC-TB-KF-60-1800
		2000	8062785	ELGC-TB-KF-60-2000
	80	200	8062786	ELGC-TB-KF-80-200
		300	8062787	ELGC-TB-KF-80-300
		500	8062788	ELGC-TB-KF-80-500
		600	8062789	ELGC-TB-KF-80-600
		800	8062790	ELGC-TB-KF-80-800
		1000	8062791	ELGC-TB-KF-80-1000
		1200	8062792	ELGC-TB-KF-80-1200
		1500	8062793	ELGC-TB-KF-80-1500
		1800	8062794	ELGC-TB-KF-80-1800
		2000	8062795	ELGC-TB-KF-80-2000

- 🗍 - Note

 $\bar{\text{Depending}}$ on the combination of motor and drive, it may not be possible to reach the maximum feed force of the drive.


Permissible axis/motor combin	nations with axial kit			Data sheets → Internet: eamm-a
Motor ¹⁾	Axial kit			
		, li li li Me	 Kits for third-party motors → Internet: eamm-a 	
Туре	Part no.	Туре		
ELGC-TB-KF-45				
With servo motor				
EMME-AS-40	4595742	EAMM-A-V32-40P		
EMMT-AS-60	4608750	EAMM-A-V32-60P		
EMME-AS-60	4608750	EAMM-A-V32-60P		
With stepper motor				
EMMS-ST-42	4281142	EAMM-A-V32-42A		
EMMS-ST-57	4597016	EAMM-A-V32-57A		
ELGC-TB-KF-60				
With servo motor				
EMMT-AS-60	4133487	EAMM-A-T42-60P		
EMME-AS-60	4133487	EAMM-A-T42-60P		
EMMT-AS-80	4623788	EAMM-A-T42-80P		
EMME-AS-80	4623788	EAMM-A-T42-80P		
With stepper motor	· · · · · ·			
EMMS-ST-57	4327034	EAMM-A-T42-57A		
EMMS-ST-87	4610008	EAMM-A-T42-87A		
ELGC-TB-KF-80				
With servo motor				
EMMT-AS-60	4824833	EAMM-A-T46-60P		
EMME-AS-60	4824833	EAMM-A-T46-60P		
EMMT-AS-80	4624170	EAMM-A-T46-80P		
EMME-AS-80	4624170	EAMM-A-T46-80P		
EMMT-AS-100	4624227	EAMM-A-T46-100A		
EMME-AS-100	4624227	EAMM-A-T46-100A		
With stepper motor	· · · · · · · · · · · · · · · · · · ·			
EMMS-ST-87	4048771	EAMM-A-T46-87A		


1) The input torque must not exceed the max. permissible transferable torque of the axial kit.

Profile mounting EAHF-L2-...-P-S

• For mounting the axis on the side of the profile

Material: Anodised wrought aluminium alloy RoHS-compliant





Dimensions and ordering data


For size	B1	B2	Β3	D1 Ø H13	D2 Ø H13	H2
45	70.6	12.8	58	5.5	10	6.1
60	85.6	12.8	73	5.5	10	6.1
80	105.6	12.8	93	5.5	10	6.1
For size	H4 ±0.1	H5	L1	Weight [g]	Part no.	Туре
45	5.5	12.2	19	6	5184133	EAHF-L2-45-P-S
60	5.5	12.2	19	6	5184133	EAHF-L2-45-P-S
					5184133	EAHF-L2-45-P-S

L

Profile mounting EAHF-L2-...-P

I have

Material: Anodised wrought aluminium alloy RoHS-compliant



• For mounting the axis on the side of the profile. The profile mounting can be attached to the mounting surface using the drill hole in the centre.

4835728

4835728

4835728

EAHF-L2-45-P

EAHF-L2-45-P

EAHF-L2-45-P

				r.			
Dimensions and For size	ordering data B1	B2	B3	D1 Ø H13	D2 Ø H13	D3 Ø	+
45	70.6	12.8	58	5.5	10	5	6
60	85.6	12.8	73	5.5	10	5	6
80	105.6	12.8	93	5.5	10	5	6
For size	H4 ±0.1	H5	L1	L2	Weight [g]	Part no. Type	

53

53

53

45

60

80

5.5

5.5

5.5

12.2

12.2

12.2

40

40

40

35

35

35

Profile mounting EAHF-L2-...-P-D...


Material: Anodised wrought aluminium alloy RoHS-compliant

Combination matrix

- For axis/axis mounting without adapter plate
- Mounting option: base axis with one-size-down assembly axis (\rightarrow page 4)

Combination matrix				
		[2] Assembly axis ELGC-BS/-TB; ELFC; EG	SC-BS	
	Size	32	45	60
[1] Base axis	45	4759748	-	-
ELGC-BS/-TB, ELFC	60	-	4759739	-
	80	-	-	4759726





Base axis
 Assembly axis

Dimensions and order	ing data					
For combination (size)	B1		B2	D1		H1
4 5/32	45		34	M4		9
6 0/45	60		47	M5		12.2
8 0/60	78		63	M6		12.2
For combination	H2	L1	L2	Weight	Part no.	Туре
(size)	±0.1			[g]		
4 5/32	3.7	51.4	42	24	4759748	EAHF-L2-25-P-D2
6 0/45	5.5	70.6	58	56	4759739	EAHF-L2-45-P-D3
8 0/60	4.5	85.6	73	77	4759726	EAHF-L2-45-P-D4


Adapter kit EHAA-D-L2

Combination matrix

Material: Anodised wrought aluminium alloy RoHS-compliant

- For axis/axis mounting with adapter plate
- Mounting option: base axis with same size or one-size-down assembly axis
 (→ page 4)
- When motors are mounted using parallel kits, this may lead to interfering contours. In this case, the adapter plate is required for height compensation (download CAD data → www.festo.com)

		[2] Assembly axis ELGC-BS/-TB; ELFC; EGSC-BS						
	Size	32	45	60	80			
[1] Base axis	45	8066714		-	-			
ELGC-BS/-TB; ELFC	60	-	8066715		-			
	80	-	-	8066716				



For combination (size)	B1	B3 ±0.05	D1	H1	Н	2	L1	L2	L3	T1	Weight [g]	Part no.	Туре
4 5/32 6 0/45	45	34 47	M4 M5	19	1	-	51.4 70.6	42 58	42 58	5.4 5.4	136 205	8066714 8066715	EHAA-D-L2-45-L2-45 EHAA-D-L2-60-L2-60
8 0/60	78	63	M6	24.2	2 1	2	85.6	73	73	6.4	315	8066716	EHAA-D-L2-80-L2-80
For combination (size)	B1	B2	B3 ±0.05	D1	H1	H2	L1	L2	L3	T1	Weight [g]	Part no.	Туре
4 5/45	45	32	34	M4	22.2	10	71	58	42	5.4	136	8066714	EHAA-D-L2-45-L2-45
6 0/60	60	39	47	M5	24.2	12	86	73	58	5.4	205	8066715	EHAA-D-L2-60-L2-60
8 0/80	78	63	63	M6	24.2	12	106	93	73	6.4	315	8066716	EHAA-D-L2-80-L2-80

Angle kit EHAA-D-L2-...-AP


Material: Anodised wrought aluminium alloy RoHS-compliant

Combination matrix

- For mounting one-size-down vertical axes (assembly axes) on base axes with mounting position "slide at top"
 - (→ page 4)

Combination matrix				
		[2] Assembly axis ELGC-BS/-TB; ELFC; EG	SC-BS	
	Size	32	45	60
[1] Base axis	45	8066718	_	_
	45	0000710	-	-
ELGC-BS/-TB; ELFC	60	-	8066719	-





Dimensions and order	ring data									
For combination (size)	B1	B2	B3	B4	B5	D1	H1	H2	H3	H4
4 5/32	69	60	34	20.5	11.5	M4	45	17.5	10	34
6 0/45	87.2	75	47	21.5	21.5	M5	60	24.5	12	47
8 0/60	107.2	95	63	23.5	23.5	M6	78	33.5	12	63
For combination (size)	H5	L1	L2	L3	T1	Weight [g]	Part no	. Type		
4 5/32	5.5	52	42	42	5.4	222	80667	18 EHA	A-D-L2-45-L2-32	2-AP
6 0/45	6.5	71	58	58	5.4	433	80667	19 EHA	A-D-L2-60-L2-4	5-AP
8 0/60	7.5	86	73	73	6.4	768	80667	20 EHA	A-D-L2-80-L2-60)-AP


Accessories


Switch lug EAPM-L2-SLS

For sensing using inductive proximity switches SIES-8M









[1] Sensor bracket [2] Proximity switch

Dimensions and ordering data


Dimensions and (oracing auta							
For size	B1	B2	B3	D1	H1	H2	H3	H4
					±0.2			
45	9.4	2	1.2±0.31	M2	37	28	5.5	3.3
60	9.7	2	1.3±0.31	M3	42	32	6.6	3.5
80	9.5	2	1.1±0.32	M4	53.5	42	8.3	4.5
For size	H5	L1	L2	L3	Weight	Part no.	Туре	
	±0.2	±0.2	±0.15		[g]			
45	33	30	24	14	18	8067260	EAPM-L2-45-SLS	
60	37	37	30	19	27	8067261	EAPM-L2-60-SLS	
80	47	44.6	36	23.4	42	8067262	EAPM-L2-80-SLS	


Sensor bracket EAPM-L2-SH

Material:

Anodised wrought aluminium alloy RoHS-compliant







[2] Proximity switch

Dimensions and ord	ering data						
For size	B1	B2	D1		H1		H2
45,60,80	5.5	1.3	M4		13.4		6
For size	H3	L1	L2	Weight	Part no.	Туре	
				[g]			
45,60,80	3	32	25	4	4759852	EAPM-	L2-SH

Accessories

Ordering data					
	For size	Description	Part no.	Туре	PU ¹⁾
Centring pin ZBS	S/centring sleeve ZBH				
	45	For slide	562959	ZBS-4	10
\bigcirc	60		189652	ZBH-5	
	80		186717	ZBH-7	
Clamping eleme	ent EADT				
	45	Tool for retensioning the cover strip	8065818	EADT-S-L5-32	1
	60,80		8058451	EADT-S-L5-70	
Push-in fitting					
	45,60,80	For sealing air connection	186266	QSM-G1/8-4-I	10
			186267	QSM-G1/8-6-I	

1) Packaging unit

Ordering data – Proximity switches for T-slot, inductive

Ordering data –	Proximity switches for T-slot, inductive					Data sheets → Internet: sies
	Type of mounting	Switching output	Electrical connection	Cable length [m]	Part no.	Туре
N/O contact						
1	Inserted in the slot from above, flush with	PNP	Cable, 3-wire	7.5	551386	SIES-8M-PS-24V-K-7,5-OE
S.	the cylinder profile		Plug M8x1, 3-pin	0.3	551387	SIES-8M-PS-24V-K-0,3-M8D
<u>e</u>		NPN	Cable, 3-wire	7.5	551396	SIES-8M-NS-24V-K-7,5-OE
			Plug M8x1, 3-pin	0.3	551397	SIES-8M-NS-24V-K-0,3-M8D
N/C contact					_	
	Inserted in the slot from above, flush with	PNP	Cable, 3-wire	7.5	551391	SIES-8M-PO-24V-K-7,5-OE
S	the cylinder profile		Plug M8x1, 3-pin	0.3	551392	SIES-8M-PO-24V-K-0,3-M8D
		NPN	Cable, 3-wire	7.5	551401	SIES-8M-NO-24V-K-7,5-OE
			Plug M8x1, 3-pin	0.3	551402	SIES-8M-NO-24V-K-0,3-M8D
Ordering data –	Proximity switches for T-slot, magneto-res	istive				Data sheets → Internet: sm
0	, , , ,		Electrical connection	Cable longth		Tune

	Type of mounting	Switching	Electrical connection	Cable length	Part no.	Туре
		output		[m]		
N/O contact						
	Insertable in the slot from above,	PNP	Cable, 3-wire	2.5	574335	SMT-8M-A-PS-24V-E-2,5-OE
BE BEE D	flush with the cylinder profile, short design		Plug M8x1, 3-pin	0.3	574334	SMT-8M-A-PS-24V-E-0,3-M8D
N/C contact						
BEE ST A	Insertable in the slot from above, flush with the cylinder profile, short design	PNP	Cable, 3-wire	7.5	574340	SMT-8M-A-PO-24V-E-7,5-OE

Ordering d	lata – Connecting cables	Data sheets → Internet: nebu			
	Electrical connection, left	Electrical connection, right	Cable length	Part no.	Туре
			[m]		
E JE	Straight socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541333	NEBU-M8G3-K-2.5-LE3
			5	541334	NEBU-M8G3-K-5-LE3
	Angled socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541338	NEBU-M8W3-K-2.5-LE3
\$			5	541341	NEBU-M8W3-K-5-LE3

Festo - Your Partner in Automation





1 Festo Inc.

5300 Explorer Drive Mississauga, ON L4W 5G4 Canada

Festo Customer Interaction Center Tel: 1 877 463 3786 Fax: 18773933786 Email: customer.service.ca@festo.com ventas.mexico@festo.com



2 Festo Pneumatic

Av. Ceylán 3, Col. Tequesquináhuac 54020 Tlalnepantla, Estado de México

Multinational Contact Center 01 800 337 8669



3 Festo Corporation 1377 Motor Parkway Suite 310 Islandia, NY 11749



4 **Regional Service Center** 7777 Columbia Road Mason, OH 45040

Festo Customer Interaction Center 1 800 993 3786 1 800 963 3786 customer.service.us@festo.com

Subject to change

f 🗾 in 🛗 www.festo.com/socialmedia

Connect with us



www.festo.com