

AWWA C515 OS&Y Resilient Seated Gate Valve

FIG. 3233

Specification

- Meet or exceed the requirements of AWWA C515 standard.
- Full Waterway.
- Adjustable Packing.
- Rubber Fully Encapsulated Ductile Iron Wedge.
- Handwheel - open left or open right.
- Face to Face Dimension complies with ASME B16.10 and EN558 Series 3.
- Flange and Drilling comply with ASTM B16.1 Class 125 or EN1092-2 PN10/16/25. (Other flange types available upon Request)
- Grooved Ends meet AWWA C606 standard or Metric Dimensions.
- Rated Working Pressure
300 psi/25 bar for 2" to 12"
250 psi/16 bar for 14" to 18"
200 psi/16 bar for 20" to 24"

Corrosion Protection

- Fusion Bonded Coating Interior and Exterior meet or exceed all applicable of AWWA C550 standard.

Material Specification

Part	Material	EN Specification	ASTM Specification
Body	Ductile Iron	EN 1563 EN-GJS-450-10	A536 Grade 65-45-12
Wedge	EPDM Fully Encapsulated Ductile Iron		
Wedge Nut	Stainless Steel	EN 10088 X5CrNi18-10	A351 Grade CF8
Bonnet	Ductile Iron	EN 1563 EN-GJS-450-10	A536 Grade 65-45-12
Stem	Stainless Steel	EN 10088 X5CrNi18-10	A276 Type 304
Yoke	Ductile Iron	EN 1563 EN-GJS-450-10	A536 Grade 65-45-12
Stem Nut	Bronze	EN 12165 CuAl10Fe3	B148 C95200
Packing	Graphite	Non-Asbestos	Non-Asbestos
Gland	Ductile Iron	EN 1563 EN-GJS-450-10	A536 Grade 65-45-12
Gland stud	Stainless Steel	EN 10088 X5CrNi18-10	F593 Grade 304
Fasteners	Carbon Steel	Grade 8.8	A307 Grade B
Gasket	Rubber EPDM	EN 681	D2000
Handwheel	Ductile Iron	EN 1563 EN-GJS-450-10	A536 Grade 65-45-12


Options

- ASTM Type 316 Stainless Steel Stem.
- Stainless Steel Fasteners: A2-70 or A4-70.
- Operated with Handwheel, Operating Nut, Gearbox or Actuator.

Main Dimensions (mm)

DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L	178	190	203	229	254	267	292	330	356	381	406	432	457	508
H(OPEN)	385	432	485	550	660	740	930	1130	1320	1165	1860	2082	2290	2692
D	184	184	254	254	305	305	356	445	445	558	558	610	610	762

Schematic



Notes

- Designs, materials and specifications shown are subject to change without notice due to the continuous development of our products.