

# Lever-Lock Handlever Actuators for Fisher™ 8560, A41, and A11 Valves

The lever-lock handlever actuator is used for reliable manual operation of NPS 3 through 8 Fisher 8560, A41, and NPS 3 and 4 A11 high-performance butterfly valves. Spring loading secures the handlever in the notched quadrant plate, allowing the valve disk to be locked in intermediate positions.

## Features

- **Rugged Construction**—Lever-lock handlever actuator consists of ductile iron quadrant plate, handle, and grip.
- **Monitoring Ease**—Lever-lock handlever configuration offers positive on/off and intermediate locked positions for throttling control.
- **Tamper Resistant**—Handle can be provided with padlock for tamper-resistant open/closed position.
- **Accessory Mounting Available**—Limit switches can be mounted to the handlever actuator for remote valve position indication.
- **Adjustable Travel Stops**—Positioning device available for setting repeatable stops from 0 to 90 degrees rotation.



W4896

Lever-Lock Handlever Actuator Mounted on Valve

## Installation

The lever-lock handlever actuator is normally mounted on a valve at the factory. However, the handlever actuator can be field-mounted. Dimensions are shown in figure 1 and table 2.

**Specifications**

<p><b>Lever-Lock handlever Actuator Sizes</b></p> <p>See table 1</p> <p><b>Valve Compatibility</b></p> <ul style="list-style-type: none"> <li>■ Accepts 8560 and A41 valve Double-D shafts from 12.7 to 25.4 mm (1/2 to 1 inches)</li> <li>■ Accepts A11 valve square-end shafts from 10.3 to 15.9 mm (13/32 to 5/8 inches)</li> </ul> <p><b>Maximum Torque Output</b></p> <p>See table 1</p>	<p><b>Handlever Length</b></p> <p>Maximum of 432 mm (17 inches). See figure 1 and table 2</p> <p><b>Construction Materials</b></p> <p>Handle, quadrant plate, and handle grip are all ductile iron</p> <p><b>Dimensions and Approximate Weights</b></p> <p>See figure 1 and table 2</p> <p><b>Options</b></p> <ul style="list-style-type: none"> <li>■ Adjustable travel stops</li> <li>■ Limits Switches</li> </ul>
---	--

Table 1. Handlever Actuator Sizes for Fisher 8560, A41, and A11 Valves Sizes, and Maximum Allowable Torque for Handlever Actuators


HANDLEVER ACTUATOR SIZE	VALVE SIZE, NPS	8560 AND A41 VALVES <sup>(1)</sup>		A11 VALVES <sup>(2)</sup>
		CL150	CL300	CL600
		Maximum Allowable Torque, N•m		
I	3	58.2 <sup>(3)</sup>	124.3	90.4
	4	124.3	---	---
II	4	---	163.9	163.9
	6	163.9	163.9	---
	6	163.9	---	---
HANDLEVER ACTUATOR SIZE	VALVE SIZE, NPS	Maximum Allowable Torque, Lbf•in		
I	3	515 <sup>(3)</sup>	1100	800
	4	1100	---	---
II	4	---	1450	1450
	6	1450	1450	---
	6	1450	---	---

1. 8560 and A41 torque values are based on S17400 (17-4PH stainless steel) H1075 stem material.  
 2. A11 torque values are based on S17400 (17-4PH stainless steel) H1025 stem material.  
 3. Do not exceed this torque regardless of actuator size.

Table 2. Handlever Actuator Dimensions and Weights

VALVE SIZE, NPS	DIMENSION			HANDLEVER ACTUATOR WEIGHT
	L	M	N	
	mm			Kg
3	114	276	76	2.3
4	114	276	76	2.3
6	117	432	97	4.1
8	117	432	97	4.1
	Inches			Lbs
3	4.50	10.88	3.00	5
4	4.50	10.88	3.00	5
6	4.62	17.00	3.81	9
8	4.62	17.00	3.81	9

Figure 1. Handlever Actuator Dimensions and Weights (also see table 2)



1287155-C

## Ordering Information

When ordering, specify:

### Application

1. Valve type number, size, and shaft diameter or shaft size with which the lever-lock handlever actuator will be used.
2. Valve disk rotation

### Actuator

Refer to table 1 for maximum output torque and select the proper size of lever-lock handlever. For service conditions that require higher torque capabilities than those listed in table 1, use a manual gear actuator.

### Valve

Refer to separate valve bulletins for ordering information.

Neither Emerson, Emerson Automation Solutions, nor any of their affiliated entities assumes responsibility for the selection, use or maintenance of any product. Responsibility for proper selection, use, and maintenance of any product remains solely with the purchaser and end user.

Fisher is a mark owned by one of the companies in the Emerson Automation Solutions business unit of Emerson Electric Co. Emerson Automation Solutions, Emerson, and the Emerson logo are trademarks and service marks of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available upon request. We reserve the right to modify or improve the designs or specifications of such products at any time without notice.

Emerson Automation Solutions  
Marshalltown, Iowa 50158 USA  
Sorocaba, 18087 Brazil  
Cernay, France 68700  
Dubai, United Arab Emirates  
Singapore 128461 Singapore

[www.Fisher.com](http://www.Fisher.com)

